







Sloan® Sensor Flushometer

SLOAN 186 SFSM

Product description

Sloan® Exposed Sensor Urinal Flushometer.

Compliances & Certifications





















(ADA Compliant, BAA Compliant, BABAA Compliant, BREEAM Water Credit, cUPC Certified, Green Globes Water, IAPMO, LEED Water, Satisfies LEED Credits, UL Certified, USA, EPA WaterSense Listed)

Listed compliances and certifications may vary based on product variation.

Finish



Available in Polished Chrome (CP).

Downloads

- Sloan Exposed Installation Instructions
- Sloan Exposed (Spanish) Installation Instructions
- BBV-500_550-A Installation Instructions
- Ontrol Stop Repair and Maintenance Guide
- 7 Flush Connections Flanges Repair and Maintenance Guide
- https://cdn.pimber.ly/public/asset/
- Additional Downloads

Videos

Sloan - Company Overview

Features

- Flush volumes start as low as 1.0 gpf/3.8 Lpf
- Water conservation is aided by the ADA-compliant, non-holdopen handle, which prevents urinal from exceeding intended flush volume
- Flush accuracy is controlled by CID™ technology, also enhancing water efficiency
- · Non-Hold-Open True Mechanical Override Full Flush Button
- Integrity of the product is maintained with the vandal-resistant stop cap
- Durability is facilitated with high copper, low zinc brass castings for dezincification resistance
- Adjustable tailpiece to accommodate different height requirements
- High chloramine resistant PERMEX® Synthetic Rubber Diaphragm with Linear Filtered Bypass and Vortex Cleansing Action
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037

Warranty

View Warranty Information

Notes

All information contained within this document subject to change without notice.



Featured projects



Globe Life Field Arlington, TX

View project >

