

### **OPTIONS**

#### Flush Volume

1.6 gpf (6.0 Lpf) (1.6) 3.5 gpf (13.2 Lpf) (3.5)

# **Water Efficiency**

Low Consumption Water Saver

#### Handle

Saniguard®

## **Control Stop**

Less (L/STOP)

#### Offset

1 ½" (38mm) (1-1/2-OFST) 2" (51mm) (2-OFST)

### **Bumper**

Double Wall (YI)

# **Compliances & Certifications**

ADA Compliant BAA Compliant BABAA Compliant UPC Certified cUPC Certified

# **NOTES**

For product line drawings, view model-specific spec sheets.

All information contained within this document subject to change without notice.



### **DESCRIPTION**

Royal® Exposed Manual Specialty Water Closet Bedpan Washer Flushometer

## **FEATURES**

- Exposed water closet, diaphragm model Flushometer is intended for floor-mounted or wall-hung top spud bowls
- Operates by means of a metal oscillating, non-hold-open handle with a triple seal handle packing to ensure water conservation
- Presents a leaner, more aesthetic installation, reducing possible bacteria growth on hidden and hard-to-reach surfaces found on other bedpan washer units
- Eliminates the need for unsanitary hose sprays, as well as the additional housekeeping that hoses require and the potential for patient slippage
- Valve body, stop body, diverter body and diverter pivot made from brass casting using semi-red brass for durability and long life
- PERMEX synthetic rubber diaphragm with Dual Filtered Fixed Bypass
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

# **DOWNLOADS**

- Slimline Royal/Regal XL Exposed Installation Instructions
- Control Stop Repair and Maintenance Guide
- Flush Connections Flanges Repair and Maintenance Guide
- Tail Piece Repair and Maintenance Guide
- Royal Manual Diaphragm Flushometer Repair and

Sloan 10500 Seymour Ave, Franklin Park, IL 60131



Maintenance Guide

- Slimline Bedpan Washer Repair and Maintenance Guide
- Additional Downloads