



DropSpot™ Bottle Filler & Water Cooler

DRS100

Product description

, DropSpot™ On-wall Bottle Filler.

Compliances & Certifications



(ASME A112.18.1 Compliant, FCC Compliant, IAPMO, IAPMO listed ASME, IGC 115, IGC 226, MA Approved, Meets Canada OBC and QBC, NSF-61/CAN-61, NSF-372 Lead Free, AB100, NSF/ANSI/CAN 61: Q ≤ 1.0, TAS, UL 399/CSA C22.2 No.120, UL Certified (US and Canada), cUPC Certified)

Code 33820001

Finish

 304 Stainless Steel (SS)

Downloads

-  DRS100-REF Stand Alone Refrigerated Bottle Filler Installation Instructions.pdf
-  DRS100-UNREF Stand Alone Unrefrigerated Bottle Filler Installation Instructions.pdf
-  FA3000-DRS100 Filter Assembly Installation Instructions.pdf
-  RC8000 Remote Chiller for DRS-100 Bottle Filler Installation Instructions.pdf
-  FC3000 Replacement Water Filter Cartridge Installation Instructions.pdf
-  Additional Downloads

Videos

-  Sloan DropSpot™ Bottle Fillers and Water Coolers
-  Sloan DropSpot™ Bottle Fillers and Water Coolers Now at Wrigley Field

Details

- Mounting: On-wall
- Configuration: Bottle Filler
- Filter Option: Unfiltered (UNFIL)
- Refrigeration Option: Refrigerated (REF)
- Finish: 304 Stainless Steel (SS)
- Chilling Capacity: 8.0 gph (30.3 Lph)
- Full Load Amps: 5.3
- Length: 7.9 (201mm)
- Width: 19 (483mm)
- Height: 51.4 (1306mm)
- Weight: 106lbs (48kg)
- Installation Location: Indoor
- Bottle Filler Water Flow Rate: Up to 1.2 gpm (4.5 Lpm)

Features

Sloan On-wall Bottle Filler is available in both Stainless and Black, filtered and unfiltered, refrigerated and unrefrigerated options.

- Touch-free sensor operated bottle filler with 20 second max run time
- All models IoT compatible with subscription to SC Argus® Pro SaaS - Remotely monitor water usage and receive filter replacement notifications, helping simplify maintenance across one or multiple facilities
- Schedule and document automated line flushes through SC Argus Pro to support water quality programs and reduce manual maintenance
- ADA compliant when installed in accordance with applicable requirements
- Laminar flow water supply provides up to 1.2 gpm fill rate for quick fill
- Swing-open cabinet provides easy access to filter
- Soft ambient white light to indicate filter status
- Backlit LED light that illuminates bottle filling area when sensor is activated
- Bottle Counter Display indicates the number of 16 oz plastic bottles saved as well as the ounces of water dispensed for water consumption tracking
- Rough-in matches other manufacturers' recommended rough-in locations for easy replacement

OPTIONAL: A water filter upgrade can be added to this unit (part number 33830001). Sold separately

Recommended specifications

Sloan's DropSpot™ On-wall Bottle Filler Unfiltered Refrigerated Stainless. Chilling capacity of 8.0 gph of 50F drinking water, based on 80F inlet water and 90F ambient. Bottle filler shall include sensor operated activation with a 20 second maximum run time. Bottle counter display indicates the number of 16 oz plastic bottles saved as well as the ounces of water dispensed for water consumption tracking. White light indicates the water filter status. Unit shall include LED lights that illuminate the bottle filling area. Bottle filler housing construction shall be stainless steel with a satin finish. Bottle filler shall provide up to 1.2 gpm flow rate with a laminar flow. Cabinet door shall have swing-open mechanism, providing easy access for filter replacement.

Power

- (Standard) 115VAC
- 60Hz
- 5.3A
- Provide Duplex Receptacle on GFCI Protected Circuit

Warranty

[View Warranty Information](#)

Notes

All information contained within this document subject to change without notice.

