

ECOS® Sensor Flushometer

ECOS 111

Product description

ECOS® Exposed Sensor Hardwired Water Closet Flushometer.

Compliances & Certifications

(ADA Compliant*, BAA Compliant, BABAA Compliant, BREEAM Water Credit, Green Globes Water, IAPMO, LEED Water, Satisfies LEED Credits, EPA WaterSense Listed)

Listed compliances and certifications may vary based on product variation.

Finish

Available in Polished Chrome (CP), Graphite (GR), Brushed Stainless (SF), Brushed Nickel (BN).

Downloads

- Sloan ECOS Single_Dual-Flush Flushometer & Retrofit Valve Installation Instructions
- ECOS HW Repair and Maintenance Guide
- Control Stop Repair and Maintenance Guide
- Additional Downloads

Videos

- Sloan – Company Overview

⚠ WARNING: Cancer and Reproductive Harm – www.P65Warnings.ca.gov

Sloan 10500 Seymour Ave, Franklin Park 800.982.5839 sloan.com

Features

Sensor operated, diaphragm type, exposed water closet flushometer for floor mounted or wall hung top spud bowls.

- Employs an infrared sensor with multiple-focused, lobular sensing fields for high and low target detection
- User-friendly, three-second flush delay
- High copper, low zinc brass castings for dezincification resistance
- Fixed metering bypass and no external volume adjustment to ensure water conservation
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037

Warranty

View Warranty Information

Notes

All information contained within this document subject to change without notice.

*Compliant with ADA accessibility requirements when installed according to ADA standards.

Featured projects



PLATFORM Night Club
Des Moines, IA

View project >