



Sloan® Solenoid (less sensor) Flushometer

8603-ESM-HW

Product description

Sloan® Concealed Solenoid (less sensor) Hardwired Water Closet PWT Flushometer.

Finish

Downloads

- [8603-ESM Installation Instructions](#)
- [8603-ESM Maintenance Guide](#)
- [Programmed Water Technologies \(PWT\) Brochure](#)
- [Additional Downloads](#)

Videos

- [Sloan – Company Overview](#)

Features

- Sloan® Prison Flushometers feature all the performance benefits of standard concealed, diaphragm model Flushometers with added durability to withstand rough environments
- Various flush volumes available to match with existing fixtures and meet water-efficiency goals
- Choose from Flushometers intended for use with stainless-steel water closet fixtures from Acorn®, Bradley®, Metcraft® and other manufacturers
- PERMEX® Synthetic Rubber Diaphragm with Dual Filtered Fixed Bypass
- Vandal-proof, push-button operation designed with non-hold-open feature to keep fixture from surpassing intended water consumption
- Adjustable tailpiece accommodates various installation heights
- High chloramine resistant PERMEX® Synthetic Rubber Diaphragm with Linear Filtered Bypass and Vortex Cleansing Action
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037
- Hardwire with battery backup
- Programmable for 2 activation in 5 minutes, lockout time options, dorm option, custom programs available

Warranty

[View Warranty Information](#)

Notes

All information contained within this document subject to change without notice.

