



Optima® Sensor Faucet

EBF-415-BAT-TEE-SF-0.5GPM-MLM-FCT

Product description

Bluetooth, Trim Plate: None, Battery Power Supply, Back-Check Tee, Brushed Stainless Finish, 0.5 gpm, Multi-Laminar Spray, Infrared Sensor, Optima® Battery or Turbine-Powered Deck-Mounted Low Body Faucet.

Compliances & Certifications

























(ADA Compliant, ASME A112.18.1 Compliant, CalGreen Compliant, CEC Compliant, EPD, GPC 0.25 or less, HPD, IAPMO, NSF-61/CAN-61, NYC604.4, Proposition 65, TAS, UPC Low Lead Certified, WELL Building Standard)

Code 3315392BT

Finish



Brushed Stainless (SF)

Connectivity



Bluetooth with Sloan Connect App

Downloads

- Faucet Spray Heads Repair and Maintenance Guide.pdf
- Optima EBF-415 _ ETF-410 Repair & Maintenance Guide and Parts Breakdown MS 8-19-24.pdf
- 7 Trim Plate Guide.pdf
- Additional Downloads

Videos

- Sloan Optima Below Deck Faucet
- Sloan Connect App[®]
- PVD Special Finishes

Product Information

EBF-415-BAT-TEE-SF-0.5GPM-MLM-FCT

Details

• Flow Rate: 0.5 gpm (1.9 Lpm) (0.5GPM)

· Spray Type: Multi-Laminar (MLM)

· Sensor Type: Infrared

Mounting Type: Single Hole

Mounting Size: Single Hole 1-1/4" to 1-1/2"

· Trim Plate: None

• Power Supply: Battery (BAT)

Temperature Mixer: Back-Check Tee (TEE)

Finish: Brushed Stainless (SF)Factory Default Timeout: 30s

· Factory Default GPC: 0.25 gpc

Features

Commercial Grade, ADA Compliant, Electronic, Sensor-Activated, Hand Washing Faucet with the following features:

- · Commercial Grade Faucet
- · ADA Compliant
- · Cast Brass Spout
- · Quick Connect Fittings
- · Integrated Water Shut-off
- Wireless Settings Adjustment
- · On-demand or Metered activation
- · Hygienic Line Flush
- · Water Usage and Battery Strength Reporting
- · Self-adapting Sensor
- · Brushed Stainless Finish

Recommended specifications

Faucet shall include cast brass body, quick-connect fittings, twist-off/shut-off solenoid assembly, removable battery cartridge, flexible power supply and allow adjustment of settings wirelessly via Apple or Android smartphones.

Electrical specifications

- Sensor Range: 4"-5" (102-127 mm)
- · Timeout Adjustment Setting: 30 Seconds

Warranty

View Warranty Information

Notes

All information contained within this document subject to change without notice.

Looking for other variations of the EBF-415 product? View the general spec sheet with all options.

Find a matching soap dispenser for this faucet.

Find a compatible sink for this faucet







