



Sloan® XLERATOR® Hand Dryer

EHD-502-ECO-MW-HEPA

Product description

EHD-502-ECO, HEPA, 208/277V, Sloan® XLERATOR® Sensor-Operated Wall-Mounted Hand Dryer.

Compliances & Certifications



(BAA Compliant, cUL Certified, EPD, Proposition 65, UL Certified, WELL Building Standard)

Code 3366110

Finish



Matte White (MW)

Downloads

- [Sloan XLERATOR and Sloan XLERATOR Eco Hand Dryer Instructions .pdf](#)
- [Hand Dryer Brochure.pdf](#)
- [Additional Downloads](#)

Videos

- [Sloan – Company Overview](#)

Details

- Finish: Matte White (MW)
- Voltage: 208/277V
- Wattage: 50/60Hz
- Amperage: 2.0A-2.2A
- Mounting: Wall-Mounted
- Power Type: Hardwired
- Depth: 6.6875" (322mm)
- Height: 6.6875" (170mm)
- Width: 11.75" (298mm)

Features

- Automatically operates by means of an Infrared Optical Sensor with 35-second lockout feature, it activates a strong controlled air blast
- Residual moisture is evaporated with a warm stream of air up to 135°F/57°C
- One-piece heavy-duty rib reinforced die cast zinc alloy housing minimizes damage to dryer in abusive environments
- 95% cost savings vs. paper towels
- Can be easily positioned to comply with ADA requirements or for juvenile height
- Hygienic hand dryer solution, 10 second dry time
- Available with Recess Kit for ADA compliance
- Can install multiple units on one circuit
- Virtually maintenance free
- Available with HEPA Filtration System proven to remove 99.97% of potentially present bacteria at 0.3 microns from the air

Recommended specifications

Sloan Xlerator Sensor Operated Hand Dryer. 208V/230V Matte White Finish.

Warranty

[View Warranty Information](#)

Notes

All information contained within this document subject to change without notice.

