



Elongated Floor-Mounted ADA Pressure Assist Water Closet

WETS-8029.8018

Product description

Standard, Floor-Mounted 0.75 gpf (2.8 lpf) ADA 12" Rough-in Left Handle.

Compliances & Certifications



(BAA Compliant, CalGreen Compliant, CEC Compliant, LEED Water, EPA WaterSense Listed)

Code 80298018

Downloads

- [Pressure-Assisted Toilets Installation Instructions.pdf](#)
- [Flushmate Owner's Manual.pdf](#)
- [Pressure-Assisted Toilets Repair and Maintenance Guide.pdf](#)
- [Pressure-Assisted Toilets Brochure.pdf](#)
- [Fixture Brochure.pdf](#)
- [Additional Downloads](#)

Videos

- [Sloan - Company Overview](#)

Details

- Flush Volume: 0.75 gpf (2.8 lpf)
- Handle Side: Left

Features

- White Vitreous China
- Elongated bowl
- Floor mounted, floor outlet
- 12" (305mm) rough-in
- Chrome metal flush handle
- Secure, anti-rocking 3-point tank mounting system
- Powered by Flushmate® brand pressure-assist flushing technology to achieve 900g MaP score
- Over 60 ft (18.3 m) drainline carry performance
- Water spot area: 11 ¼ x 9 ¾ (286 mm x 248 mm)
- Smooth, quiet cable activated flush handle - left hand
- Fully glazed trapway
- Closet bolts and caps included
- Toilet seat and wax ring not included
- Tank and bowl are packed in a single carton
- ADA compliant

Components

- Bowl: Code 2108029
- Tank: Code 2108018

Recommended Seats

- Bemis - 1955CT/1955SSCT & 2155CT/2155SSCT
- Church - 295CT/295SSCT & 2155CT/2155SSCT

Warranty

[View Warranty Information](#)

Notes

All information contained within this document subject to change without notice.

Static load tested according to the procedure outlined in Section 6.7 of ASME A112.19.2. Not recommended for bariatric use. @ AttributePlainHyperlinks: Find a compatible flushometer for this water closet

WaterSense compliant when used with a WaterSense compliant flushometer.

All vitreous china dimensions shown in these drawings are nominal and not to scale. Dimensions can vary within the tolerances established in the governing ASME A112.19.2/CSA B45.1 standard. It is important to consider this when planning rough-in and plumbing layouts.

