

OPTIONS**Power Type**

Battery
Turbine

Body Type

Mid

Mounting

Deck

Power Supply

Battery (BAT)
Battery + Turbine (TUR)

Sensor Type

Infrared

Flow Rate

0.5 gpm (1.9 Lpm) (0.5GPM)
0.35 gpm (1.3 Lpm) (0.35GPM)
1.5 gpm (5.7 Lpm) (1.5GPM)

Spray Type

Multi-Laminar (MLM)
Laminar (LAM)

Trim Plate

4" (102mm) (4)
8" (203mm) (8)

Finish

Polished Chrome (CP)

Control Access

Below Deck

Mixer

Back-Check Tee (TEE)
Above Deck Mixer (ADM)
Below Deck Manual Mixing Valve (BDM)
Below Deck Thermostatic Mixing Valve (BDT)

Special Features

Less Logo (LL)

Compliances & Certifications

ADA Compliant
ASME A112.18.1 Compliant
CEC Compliant
EPD
HPD



Image for a standard EBF-187 shown

DESCRIPTION

Optima® Battery or Turbine-Powered Deck-Mounted Mid Body

FEATURES

- Commercial Grade Faucet
- ADA Compliant
- Cast Brass Spout
- Quick Connect Fittings
- Integrated Water Shut-off
- Wireless Settings Adjustment
- On-demand or Metered activation
- Hygienic Line Flush
- Water Usage and Battery Strength Reporting
- Self-adapting Sensor

SMART FAUCET ADDITIONAL OPTIONS

- 24VAC plug adapter, power harness assembly or box mount power supply
- Multi-unit gang adapter kit
- 110V or 230V/6VDC plug adapter
- Special PVD finishes available Brushed Stainless, Brushed Nickel, Polished Brass and Matte Black

DOWNLOADS

- [Optima Smart Faucet Below Deck Installation Instructions](#)
- [Faucet Spray Heads Repair and Maintenance Guide](#)
- [ETF-80/880 and EBF-85/187 Below Deck Repair and Maintenance Guide](#)
- [Trim Plate Guide](#)
- [Additional Downloads](#)

IAPMO
NSF-61
Proposition 65
TAS
UPC Certified

VIDEOS

-  Sloan Connect App®
-  Sloan Optima Below Deck Faucet

NOTES

For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.

[Find a matching soap dispenser](#) for this faucet.

[Find a compatible sink](#) for this faucet.