

OPTIONS

Flush Volume

- 1.6/1.1 gpf (6.0/4.2 Lpf) (1.6/1.1)
- 1.28 gpf (4.8 Lpf) (1.28)
- 1.28/1.1 gpf (4.8/4.2 Lpf) (1.28/1.1)

Finish

- Polished Chrome (CP)
- Brushed Stainless (SF)

Power Type

- Battery
- Hardwired (HW)

Activation

- Sensor

Valve

- Diaphragm

Water Efficiency

- High Efficiency

Bypass

- Dual-Filtered Bypass

Fixture Type

- Water Closet

Fixture Connection

- Top Spud

Installation

- Exposed

Override

- Electrical

Handle

- Less Handle Body (LH)

Control Stop

- No (XD)

Special Features

- Fits †Zurn® valve bodies (Z)

Specialty

- Retrofit

Compliances & Certifications

- BREEAM Water Credit
- cUPC Green Certified
- ADA Compliant



Image for a standard ECOS RESS-C shown

DESCRIPTION

ECOS® Exposed Sensor Water Closet Retrofit Flushometer

FEATURES

- Valve shall be in compliance to the applicable sections of ASSE 1037

DOWNLOADS

- [Sloan ECOS Single/Dual-Flush Flushometer & Retrofit Valve Installation Instructions](#)
- [Control Stop Repair and Maintenance Guide](#)
- [Flush Connections Flanges Repair and Maintenance Guide](#)
- [Tail Piece Repair and Maintenance Guide](#)
- [ECOS Repair and Maintenance Guide](#)
- [ECOS HW Repair and Maintenance Guide](#)
- [Additional Downloads](#)

Green Globes Water Credit
cUPC Certified
BABAA Compliant
BAA Compliant
Carbon Neutral
EPD
HPD

NOTES

For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.

† The brands and/or products names referenced herein may be subject to trademark rights of their respective owners. Use of the brands and names is for identification purposes only and does not imply affiliation with or endorsement by Sloan.