

OPTIONS

Flush Volume

1.28/1.1 gpf (4.8/4.2 Lpf) (1.28/1.1)

1.6/1.1 gpf (6.0/4.2 Lpf) (1.6/1.1)

Finish

Brushed Nickel (BN)

Brushed Stainless (SF)

Graphite (GR)

Polished Brass (PB)

Polished Chrome (CP)

Water Efficiency

High Efficiency

Low Consumption

Compliances & Certifications

ADA Compliant

BAA Compliant

Satisfies LEED Credits

UPC Certified

BABAA Compliant

LEED V4 Water Efficiency Credit

WaterSense Listed

cUPC Certified

cUPC Green Certified

NOTES

For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.



Image for a standard ECOS RESS-C BT DF shown

DESCRIPTION

ECOS® Exposed Sensor Water Closet Retrofit Flushometer

FEATURES

- Wireless connected device for real time diagnostic and adjustable product settings
- Sloan Connect App® readily available for smart phone and tablet devices
- User friendly three (3) second Flush Delay
- "Low Battery" Flashing LED
- Sweat solder adapter with cover tube and cast wall flange with set screw
- Four (4) Size AA Battery Power Source
- Operates by means of an infrared sensor with multiple-focused, lobular sensing fields for high and low target detection
- Fixed Metering Bypass and No External Volume Adjustment to Ensure Water Conservation
- Flex Tube Diaphragm designed for improved life and reduced maintenance
- Engineered Metal Cover with replaceable Lens Window
- PERMEX® Synthetic Rubber Diaphragm with Dual-Filtered Fixed Bypass
- Courtesy Flush® Override Button
- Valve shall be in compliance to the applicable sections of ASSE 1037

DOWNLOADS

- [Sloan ECOS Single/Dual-Flush Flushometer & Retrofit Valve Installation Instructions](#)
- [Control Stop Repair and Maintenance Guide](#)
- [Flush Connections Flanges Repair and Maintenance Guide](#)

Sloan 10500 Seymour Ave, Franklin Park, IL 60131

Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com

- [Tail Piece Repair and Maintenance Guide](#)
- [Additional Downloads](#)

VIDEOS

-  [Sloan Connect App®](#)
-  [PVD Special Finishes](#)