



## Optima® Sensor Faucet

ETF-420-BOX-BDM-CP-0.5GPM-MLM-BAA-FCT

### Product description

Trim Plate: None, Box Transformer Power Supply, Below Deck Manual Mixing Valve, Polished Chrome Finish, 0.5 gpm, Multi-Laminar Spray, Infrared Sensor, Optima® Hardwired-Powered Deck-Mounted Mid Body Faucet.

### Compliances & Certifications



(ADA Compliant\*, ASME A112.18.1 Compliant, BAA Compliant, CalGreen Compliant, CEC Compliant, EPD, GPC 0.25 or less, HPD, IAPMO, NSF-61/CAN-61, NYC604.4, TAS, UPC Low Lead Certified, WELL Building Standard)

### Code 3365818BT

#### Finish



#### Connectivity



#### Downloads

- Optima Smart Faucet Below Deck Installation Instructions.pdf
- Faucet Spray Heads Maintenance Guide.pdf
- Optima EBF-425 \_ ETF-420 Repair & Maintenance Guide and Parts Breakdown.pdf
- Trim Plate Guide.pdf
- Additional Downloads

#### Videos

- Sloan Optima Below Deck Faucet
- Sloan Connect App®
- PVD Special Finishes

## Details

- Flow Rate: 0.5 gpm (1.9 Lpm) (0.5GPM)
- Spray Type: Multi-Laminar (MLM)
- Sensor Type: Infrared
- Mounting Type: Single Hole
- Mounting Size: Single Hole 1-3/16"
- Trim Plate: None
- Power Supply: Box Transformer (BOX)
- Temperature Mixer: Below Deck Manual Mixing Valve (BDM)
- Finish: Polished Chrome (CP)
- Factory Default Timeout: 30s
- Factory Default GPC: 0.25 gpc

## Features

Commercial Grade, ADA Compliant, Electronic, Sensor-Activated, Hand Washing Faucet with the following features:

- Commercial Grade Faucet
- ADA Compliant
- Cast Brass Spout
- Quick Connect Fittings
- Integrated Water Shut-off
- Wireless Settings Adjustment
- On-demand or Metered activation
- Hygienic Line Flush
- Water Usage and Battery Strength Reporting
- Self-adapting Sensor
- Chrome plated finish

## Recommended specifications

Faucet shall include cast brass body, quick-connect fittings, twist-off/shut-off solenoid assembly, removable battery cartridge, flexible power supply and allow adjustment of settings wirelessly via Apple or Android smartphones.

## Electrical specifications

- Sensor Range: 4"-5" (102-127 mm)
- Timeout Adjustment Setting: 30 Seconds

## Power Supply Options

- 24VAC Box Transformer (included with BOX models)/0345370PK

## Warranty

[View Warranty Information](#)

## Notes

All information contained within this document subject to change without notice.

\*Compliant with ADA accessibility requirements when installed according to ADA standards.

Looking for other variations of the ETF-420 product? [View the general spec sheet with all options.](#)

[Find a matching soap dispenser](#) for this faucet.

[Find a compatible sink](#) for this faucet

