



SOLIS® Sensor Flushometer

SOLIS RESS-U SMT-0.25-CP

Product description

0.25 gpf, SC Argus™ Pro Compatible, Dual-Filtered Fixed Bypass Diaphragm, Polished Chrome Finish, Fixture Connection Top Spud, Single Flush, Electrical Override, Solar, Infrared, 10.5" Vacuum Breaker, SOLIS® Exposed Sensor Urinal Retrofit Flushometer.

Compliances & Certifications



(ADA Compliant, cUPC Green Certified, EPD, FCC Compliant, HPD, IAPMO, LEED Water)

Code 33753016

Finish

 Polished Chrome (CP)

Connectivity

IoT - SC Argus™ Pro Compatible

Downloads

-  [Control Stop Repair and Maintenance Guide.pdf](#)
-  [Flush Connections Flanges Repair and Maintenance Guide.pdf](#)
-  [Tail Piece Repair and Maintenance Guide.pdf](#)
-  [Additional Downloads](#)

Videos

-  [SC Argus™ Pro](#)

Details

- Flush Volume: 0.25 gpf (0.9 lpf)
- Finish: Polished Chrome (CP)
- Power Type: Solar
- Valve: Diaphragm
- Bypass: Dual-Filtered Fixed Bypass Diaphragm
- Fixture Type: Urinal
- Fixture Connection: Top Spud
- Program: SC Argus™ Pro Compatible
- Override: Electrical
- Vacuum Breaker: 10.5"

Features

- Quiet, Exposed, Sloan Solis® Single Flush, Solar Powered, Sensor Activated Urinal RESS
- Solar Powered- The sensor assembly is powered by a solar cell that will harvest power from the artificial indoor light (incandescent, fluorescent or LED), and use it as the energy source. The solar cell can provide approximately 100% power with 650 illuminance (lux).
- Four (4) Size AA Battery Back-up Power Source with "Low Battery" Flashing LED
- Operates by means of an infrared sensor with multiple-focused, lobular sensing fields for high and low target detection
- Fixed Metering Bypass and No External Volume Adjustment to Ensure Water Conservation
- Engineered Metal Cover with replaceable Lens Window
- PERMEX® Synthetic Rubber Diaphragm with Dual Filtered Fixed Bypass
- Courtesy Flush® Override Button
- Flushometer operates normally when not connected to the SC Argus Pro system
- IOT Smart Capabilities- Compatible with Sloan's SC Argus Pro smart restroom system for wireless remote management and monitoring
- Provides detailed product information, image, model, total activations, total operating hours, location room
- Automatically sends usage data, battery life, product health information
- Allows for remote setting changes and line flushes via SC Argus Pro

Electrical specifications

- Arming Delay: 8 seconds
- Flush Delay: 3 seconds

Valve Operating Pressure (Flowing)

15-80 psi (103 - 552 kPa). Specific fixtures may require greater minimum flowing pressure - consult manufacturer requirements.

Warranty

[View Warranty Information](#)

Notes

All information contained within this document subject to change without notice.

Looking for other variations of the SOLIS RESS-U SMT product?

[View the general spec sheet with all options.](#)

[Find a compatible urinal](#) for this flushometer.

[Find a compatible water closet](#) for this flushometer.

