



Sloan® XLERATOR® Hand Dryer

EHD-501-GR

Product description

EHD-501, 110/120V, Sloan® XLERATOR® Sensor-Operated Wall-Mounted Hand Dryer.

Compliances & Certifications



(BAA Compliant, cUL Certified, EPD, Proposition 65, UL Certified, WELL Building Standard)

Code 3366061

Finish



Downloads

- [Sloan XLERATOR and Sloan XLERATOR Eco Hand Dryer Instructions .pdf](#)
- [EHD-501 Series Hand dryers Repair and Maintenance Guide.pdf](#)
- [Hand Dryer Brochure.pdf](#)
- [Additional Downloads](#)

Videos

- [Sloan – Company Overview](#)

Details

- Finish: Graphite (GR)
- Voltage: 110/120V
- Wattage: 50/60Hz
- Amperage: 11.3A-12.2A
- Mounting: Wall-Mounted
- Power Type: Hardwired
- Depth: 12.688" (170mm)
- Height: 12.688" (322mm)
- Width: 11.75" (298mm)

Features

- 8 second dry time, Weight: 15-17 lbs.
- 95% cost savings vs. paper towels
- Air temperature of up to 135°F (57°C) at a 72°F (22°C) ambient room temperature at the hands (4 inches [102 mm] below air outlet).
- Automatically operates by means of an Infrared Optical Sensor with 35-second lockout feature, it activates a strong controlled air blast
- Can be easily positioned to comply with ADA requirements or for juvenile height
- Vandal resistant cover design, Virtually maintenance free
- Electric Specifications: 110-120V – 11.3-12.2 Amps, 1240-1450 Watts, 50/60 Hz, can install multiple units on one circuit
- Externally visible Red LED light that flashes error codes to assist in troubleshooting and identify if filter has been clogged
- One-piece heavy-duty rib reinforced die cast zinc alloy housing minimizes damage to dryer in abusive environments
- Quantity Recommendations: 1 dryer for every 2 sink stations is sufficient for most applications. For high traffic applications we suggest 1 dryer per sink station.
- Suggested Mounting Heights for Ideal Performance (from floor to bottom of dryer): Men: 45" (114 cm), Women: 43" (109 cm), Teenagers: 41" (104 cm), Children: 35" (89 cm), ADA: 37" (94 cm).
Note: When mounting for any user ensure that it is mounted below the 48" ADA Maximum

Recommended specifications

Sloan Xlerator Sensor Operated Hand Dryer. 120V/110V Graphite Finish.

Warranty

[View Warranty Information](#)

Notes

All information contained within this document subject to change without notice.

