

### **OPTIONS**

#### Flush Volume

1.6 gpf (6.0 Lpf) (1.6)

1.28 gpf (4.8 Lpf) (1.28)

3.5 gpf (13.2 Lpf) (3.5)

### **Water Efficiency**

Low Consumption High Efficiency Water Saver

### **Bypass**

Dual-Filtered Fixed Bypass Diaphragm

## Vacuum Breaker

Less (XYV)

#### Offset

1 ½" (38mm) (1-1/2-OFST) 2" (51mm) (2-OFST)

#### **Bumper**

Double Wall (YI)

# **Pipe Support**

Solid Ring (YK) Split Ring (YJ)

## **Compliances & Certifications**

**ADA Compliant** 

**BAA Compliant** 

**BABAA** Compliant

Made in the USA

**UPC** Certified

cUPC Certified

Satisfies LEED Credits

WaterSense Listed

cUPC Green Certified

**BREEAM Water Credit** 

### **NOTES**

For product line drawings, view model-specific spec sheets.

All information contained within this document subject to change without notice.



## **DESCRIPTION**

Sloan® Exposed Manual Water Closet Flushometer

#### **FEATURES**

- Flush volumes start as low as 1.28 gpf/4.8 Lpf
- Water conservation is aided by the ADA-compliant, non-holdopen handle, which prevents toilet from exceeding intended flush volume
- Flush accuracy is controlled by CID<sup>™</sup> technology, also enhancing water efficiency
- Integrity of the product is maintained with the vandalresistant stop cap
- Durability is facilitated with high copper, low zinc brass castings for dezincification resistance
- Adjustable tailpiece to accommodate different height requirements
- High chloramine resistant PERMEX synthetic rubber diaphragm with Linear Filtered Bypass and Vortex Cleansing Action
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

# **DOWNLOADS**

- Sloan Exposed Installation Instructions
- Sloan Exposed (Spanish) Installation Instructions
- Control Stop Repair and Maintenance Guide
- Flush Connections Flanges Repair and Maintenance Guide
- Tail Piece Repair and Maintenance Guide
- Sloan Flushometer Repair and Maintenance Guide

Sloan 10500 Seymour Ave, Franklin Park, IL 60131



• Additional Downloads

**Sloan 10500 Seymour Ave, Franklin Park, IL 60131** Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com