



PWT™ Solenoid (less sensor) Flushometer

PWT-ESM-RESS-HR-1.28-CP-PRGM-A5-MBFW

Product description

PWT™ Concealed Solenoid (less sensor) Water Closet PWT Flushometer.

Code 33250105

Downloads

- [8603-ESM Retrofit Installation Instructions.pdf](#)
- [8603-ESM Maintenance Guide.pdf](#)
- [Programmed Water Technologies \(PWT\) Brochure.pdf](#)
- [Additional Downloads](#)

Videos

- [Sloan – Company Overview](#)

Features

- 1.28 gpf models and 1.6/2.4/3.5 gpf models
- Program set to 2 activations in 5 minutes with lockout
- Program is field changeable to 15, 30, 45 and 60 minute lockout times, or dorm setting
- Can be used with stainless-steel water closet fixtures from Acorn®, Bradley®, Metcraft® and other manufacturers
- PERMEX® Synthetic Rubber Diaphragm with Dual Filtered Fixed Bypass
- Single Flush
- Solenoid operated
- Includes standard or LED touch button for operation
- Stainless steel, vandal proof button, chemical resistant button operation designed with non-hold-open feature to keep fixture from surpassing intended water consumption
- XX' Connector cable has white arrows for easy alignment
- Hardwire power with battery backup
- 18" power cable for connection
- Use with EAF-11 plug-in transformer
- Up to 8 valve connections per EAF-11
- Four (4) Size AA Batteries
- Low Battery flashing LED
- Retrofit Kit for-
 - Manual flushometers:
 - - Royal 603
 - - Royal 611
 - - Royal 613
 - Hydraulic flushometers:
 - - Royal 9603
 - - Royal 9611
 - - Royal 9613
- Can convert other vendor's valves with addition of 3325524 EBV31A Retrofit Kit Coupling Ring

Recommended specifications

Valve shall be in compliance to the applicable sections of ASSE 1037.

Warranty

[View Warranty Information](#)

Notes

All information contained within this document subject to change without notice.

