

OPTIONS**Flush Volume**

0.125 gpf (0.5 Lpf) (0.125)

0.5 gpf (1.9 Lpf) (0.5)

Compliances & Certifications

ADA Compliant

BAA Compliant

BABAA Compliant

BREEAM Water Credit

Green Globes Water Credit

LEED V4 Water Efficiency Credit

Satisfies LEED Credits

WaterSense Listed

cUPC Certified

cUPC Green Certified

NOTESFor product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.




Image for a standard CROWN 186 SFM shown

DESCRIPTION

Crown® Exposed Sensor Urinal Flushometer

FEATURES

- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

DOWNLOADS

- [Crown Piston Type Exposed Installation Instructions](#)
- [EBV-500/550-A Installation Instructions](#)
- [Control Stop Repair and Maintenance Guide](#)
- [Flush Connections Flanges Repair and Maintenance Guide](#)
- [Tail Piece Repair and Maintenance Guide](#)
- [Crown/Crown II Repair and Maintenance Guide](#)
- [EBV500/EBV550 Repair and Maintenance Guide](#)
- [Crown Piston Assembly Repair Kit](#)
- [Additional Downloads](#)

VIDEOS

-  [Crown Piston Flushometer Basics](#)