



Retrofit Washdown Urinal

SU-1209

Product description

Standard, Vitreous China Retrofit Washdown Urinal.

Compliances & Certifications



(ADA Compliant*, BREEAM Materials Credit, CalGreen Compliant, cUPC Green Certified, EPD, Green Globes Credit, HPD, IAPMO, LEED Credit, LEED HPD, Satisfies LEED Credits, EPA WaterSense Listed)

Code 1101209

Downloads

- [Retrofit Urinal Installation Instructions.pdf](#)
- [SS:ST:SU:WETS:WEUS Fixtures Repair and Maintenance Guide.pdf](#)
- [Fixture Brochure.pdf](#)
- [Additional Downloads](#)

Videos

- [Sloan - Company Overview](#)

Details

- Nominal Dimensions: 14.5" x 20.75" x 25.25" (368 x 527 x 641mm)

Features

- Designed to maximize and complement Sloan flushometers
- Oversized footprint is ideal for retrofit jobs to cover old caulk lines
- Universal high-efficiency model works with 0.125, 0.25 and 0.5 gpf Sloan flushometers
- Thorough washdown flushing action
- Vandal resistant stainless steel strainer included
- IAPMO certified to meet or exceed ASME A112.19.2 standards
- Water Sense listed by EPA that qualifies for most rebate programs
- Meets ADA guidelines and ANSI A117.1 requirements when installed accordingly

Components

- Flushometer: Code
- Urinal: Code

Warranty

[View Warranty Information](#)

Notes

All information contained within this document subject to change without notice. @AttributePlain:*Compliant with ADA accessibility requirements when installed according to ADA standards.

