



Crown® Sensor Flushometer

CROWN 140 ESS SWB

Product description

Crown® Concealed Sensor Hardwired Water Closet Flushometer.

Finish

Downloads

-  [Royal_Sloan_Crown SWB ESS Installation Instructions](#)
-  [Optima ESS Repair and Maintenance Guide](#)
-  [Crown:Crown II Repair and Maintenance Guide](#)
-  [Additional Downloads](#)

Videos

-  [Sloan – Company Overview](#)

Features

Quiet, Concealed, Piston Type, Rough Brass Closet Flushometer with the following features:

- Fixed Volume Piston with Dual Filtered O-ring Bypass
- OPTIMA® EL-1500-L Self-Adaptive Infrared Sensor with Indicator Light
- “Walk By” Delay of Eight (8) Seconds Prevents Unintentional Flushes
- User friendly three (3) second Flush Delay
- Courtesy Flush® Override Button
- Non-Hold-Open Integral Solenoid Operator
- Die Cast Sensor Plate with no visible Fasteners (for 2-gang Electrical Box)
- 1” I.P.S. Wheel Handle Bak-Chek® Angle Stop
- Adjustable Tailpiece
- High Back Pressure Vacuum Breaker Flush Connection, Spud Coupling and Flanges for a 1½” Exposed Back Spud
- Sweat Solder Adapter
- Chrome Plated Exposed Flushometer Parts
- High Copper, Low Zinc Brass Castings for Dezincification Resistance
- Non-Hold-Open Integral Solenoid Operator, Fixed Metering Bypass and No External Volume Adjustment to Ensure Water Conservation
- Flush Accuracy Controlled by CID™ Technology
- Main Seat, Stop Seat and Vacuum Breaker molded from PERMEX® Rubber Compound for Chloramine Resistance

Warranty

[View Warranty Information](#)

Notes

All information contained within this document subject to change without notice.