



Sloan® Sensor Flushometer

SLOAN 195 ESS

Product description

Sloan® Concealed Sensor Hardwired Urinal Flushometer.

Compliances & Certifications



(BREEAM Water Credit, Green Globes Water, LEED Water, Satisfies LEED Credits)

Listed compliances and certifications may vary based on product variation.

Finish

Downloads

- [Sloan 152_195 ESS TMO Installation Instructions](#)
- [Sloan 152_195 ESS TMO Installation Instructions](#)
- [Sloan 152_140_153_195 ESS TMO SWB Installation Instructions](#)
- [Sloan:Regal ESS Repair and Maintenance Guide](#)
- [Optima ESS Repair and Maintenance Guide](#)
- [Flushometers Brochure](#)
- [Additional Downloads](#)

Videos

- [ESS Flushometer](#)

Features

- Flush volumes start as low as 1.0 gpf/3.8 Lpf
- Water conservation is aided by the ADA-compliant, non-hold-open handle, which prevents urinal from exceeding intended flush volume
- Low-consumption flush accuracy also enhances water efficiency
- Durability is facilitated with high copper, low zinc brass castings for dezincification resistance
- Adjustable tailpiece to accommodate different height requirements
- High chloramine resistant PERMEX Synthetic Rubber Diaphragm with Linear Filtered Bypass and Vortex Cleansing Action
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037

Warranty

[View Warranty Information](#)

Notes

All information contained within this document subject to change without notice.