



BASYS® Sensor Faucet

EFX-375-SOL-TEE-CP-0.35GPM-MLM-FCT

Product description

Trim Plate: None, Solar Power Supply, Back-Check Tee, Polished Chrome Finish, 0.35 gpm, Multi-Laminar Spray, Infrared Sensor, BASYS® Solar-Powered Deck-Mounted Low Body Faucet.

Compliances & Certifications



(ASME A112.18.1 Compliant, BREEAM Water Credit, CalGreen Compliant, CEC Compliant, EPD, GPC 0.25 or less, HPD, LEED Water, NYC604.4, Satisfies LEED Credits, TAS, WELL Building Standard)

Code 33243171

Finish

 Polished Chrome (CP)

Downloads

-  EFX 3Xx_6Xx Active IR Installation Instructions.pdf
-  EFX 3Xx_6Xx Active IR (SP) Installation Instructions.pdf
-  Trim Plate Guide.pdf
-  IR FAQs Repair and Maintenance Guide.pdf
-  Sloan BASYS Brochure.pdf
-  Additional Downloads

Videos

-  Sloan Connect App®
-  BASYS® Faucet Installation and Features
-  BASYS® Faucet Installation Low Height Model

Details

- Flow Rate: 0.35 gpm (1.3 Lpm) (0.35GPM)
- Spray Type: Multi-Laminar (MLM)
- Sensor Type: Infrared
- Mounting Type: Single Hole
- Mounting Size: Single Hole 1"
- Trim Plate: None
- Power Supply: Solar (SOL)
- Temperature Mixer: Back-Check Tee (TEE)
- Finish: Polished Chrome (CP)
- Factory Default Timeout: 10s
- Factory Default GPC: 0.175 gpc

Features

Commercial Grade, ADA Compliant, Electronic, Sensor-Activated, Die-Cast Metal Hand Washing Faucet with the following features:

- One tool service
- Solenoid housed in removable carrier that includes supply strainer
- Integral water supply shut off
- Vandal resistant spray insert, key housed inside faucet body
- All electronics sealed to IP-67
- Gold plated electrical contacts
- Above deck individual diagnostic indicators for battery life, solenoid condition, and power-up mode
- Flexible, high pressure supply hose, 3/8" compression connections
- Bi-stable magnetic solenoid
- Four (4) "AA" alkaline batteries (act as back-up)
- Double infrared sensors with automatic setting feature
- Single hole installation (pedestal)
- Includes all mounting hardware
- 3 year limited warranty
- Chrome plated finish

Recommended specifications

Sloan BASYS Model No. EFX-375-SOL-CP-0.35GPM-MLM-IR-FCT Infrared Sensor Activated Electronic Handwashing Faucet for pretempered or hot/cold water supplies. Product to have double infrared sensors with automatic setting feature. Solenoid valve housed in removable carrier that closes water supply upon removal eliminating, need to access control stops. Solenoid carrier includes strainer for easy above deck service. Thermostatic mixer ordered separately to comply with ASSE 1070 requirements. The product shall be tested and certified to industry standards: ASME A112.18.1M, CSA B125.1, California Health and Safety Code 116875

Electrical specifications

- Battery Life: 3 years 8,000 cycles/month
- Optional power harvesting significantly extends service life
- Sensor Range: 4" -5" (102-127 mm)
- Timeout Adjustment Setting: 10 Seconds

Warranty

[View Warranty Information](#)

Notes


All information contained within this document subject to change without notice.

Looking for other variations of the EFX-375 product? [View the general spec sheet with all options.](#)


[Find a matching soap dispenser](#) for this faucet.

[Find a compatible sink](#) for this faucet

EFX-375.10X.0X00 Faucet with Hot & Cold Water Supply



EFX-375.00X.0X0X Faucet with Single Line Water Supply



EFX-375.50X.0X00 Faucet with Hot & Cold Water Supply

