



SOLIS® Sensor Flushometer

SOLIS 8111

Product description

SOLIS® Exposed Sensor Water Closet Flushometer.

Compliances & Certifications



(ADA Compliant*, BAA Compliant, BABAA Compliant, BREEAM Materials Credit, BREEAM Water Credit, EPD, Green Globes Credit, Green Globes Water, HPD, IAPMO, LEED Credit, LEED HPD, LEED Water, Satisfies LEED Credits, cUPC Certified, EPA WaterSense Listed, WELL Building Standard)

Listed compliances and certifications may vary based on product variation.

Finish



Available in Polished Chrome (CP), Graphite (GR), Brushed Stainless (SF), Brushed Nickel (BN), Polished Brass (PB), Brushed Brass (BB).

Downloads

- [Solis 8100 Series Installation Instructions](#)
- [Solis 8100 Series \(Spanish\) Installation Instructions](#)
- [Control Stop Repair and Maintenance Guide](#)
- [Flush Connections Flanges Repair and Maintenance Guide](#)
- [Flushometer Pressure Gauges](#)
- [Finishes Brochure](#)
- [Additional Downloads](#)

Videos

- [PVD Special Finishes](#)

Features

- State-of-the-art photovoltaic technology delivers solar operation
- User friendly three (3) second Flush Delay
 - “Low Battery” Flashing LED
 - Solar Powered- The sensor assembly is powered by a solar cell that will harvest power from the artificial indoor light (incandescent, fluorescent or LED), and use it as the energy source. The solar cell can provide approximately 100% power with 650 illuminance (lux).
 - Operates by means of an infrared sensor with multiple-focused, lobular sensing fields for high and low target detection
 - Four (4) Size AA Battery Back-up Power Source
 - Fixed Metering Bypass and No External Volume Adjustment to Ensure Water Conservation
 - High copper, low zinc brass castings for dezincification resistance
 - Sweat solder adapter with cover tube and cast wall flange with set screw
 - PERMEX® Synthetic Rubber Diaphragm with Dual Filtered Fixed Bypass
 - Valve shall be in compliance to the applicable sections of ASSE 1037
 - Valve body, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass

Battery Specifications

Usage	4-AA Battery Service Life†			
	24 yrs	18 yrs	9 yrs	7.2 yrs
per month	500	1,000	3,000	4,000
per day	25	50	150	200

† Service life varies according to actual usage and restroom conditions
Battery shelf life: Alkaline= ~10 years - Lithium= ~25 years

* Service life varies according to actual usage & restroom conditions
Battery shelf life: Alkaline= ~10 years - Lithium= ~25 years

Warranty

[View Warranty Information](#)

Notes

All information contained within this document subject to change without notice.

*Compliant with ADA accessibility requirements when installed according to ADA standards.

Featured projects



Delta Terminal LAX
Los Angeles, CA

[View project >](#)



Fulton East
Chicago, IL

[View project >](#)