



Urinal & Flushometer Combo

WEUS-1000.1406-0.125-XL-CP-TMO

Product description

0.125 gpf, XL Sweat Solder Adapter Kit, Polished Chrome Finish, 0.75" Flush Connection, Fixture Connection Top Spud, Single Flush, 0.75" Inlet, 3/4" Control Stop, True Mechanical Override, Battery, Infrared, SU-1009 Urinal and GEM-2 186 SFMS Flushometer.

Compliances & Certifications



(ADA Compliant*, BAA Compliant, CalGreen Compliant, EPD, HPD, IAPMO, Satisfies LEED Credits, EPA WaterSense Listed, WELL Building Standard)

Code 10001406

Downloads

- [Standard Spud Urinal Installation Instructions.pdf](#)
- [GEM_GEM 2 Piston Type Exposed Installation Instructions.pdf](#)
- [EBV-500_550-A Installation Instructions.pdf](#)
- [SS:ST:SU:WETS:WEUS Fixtures Repair and Maintenance Guide.pdf](#)
- [EBV500-EBV550 Repair and Maintenance Guide.pdf](#)
- [Gem 2 Repair and Maintenance Guide.pdf](#)
- [Additional Downloads](#)

Videos

- [Sloan – Company Overview](#)

Product Information

Details

- Flush Volume: 0.125 gpf (0.5 lpf)
-

Features

- Complete urinal system including GEM2 XL flushometer Designed to maximize performance
- Thorough washdown flushing action
- Durable, hygienic vitreous china construction
- Vandal resistant stainless steel strainer included
- IAPMO certified to meet or exceed ASME A112.19.2 standards
- Water Sense listed by EPA that qualifies for most rebate programs
- Meets ADA guidelines and ANSI A117.1 requirements when installed accordingly

WEUS-1000.1406-0.125-XL-CP-TMO

Components

- Flushometer: Code 3072622
 - Urinal: Code 1101009
-

Warranty

[View Warranty Information](#)

Notes

All information contained within this document subject to change without notice.

*Compliant with ADA accessibility requirements when installed according to ADA standards.

