

OPTIONS

Flush Volume

- 1.28 gpf (4.8 Lpf) (1.28)
- 1.6/2.4/3.5 gpf (6.0/9.1/13.2 Lpf) (1.6/2.4/3.5)

Water Efficiency

- Low Consumption

Push Button

- Metal Button Fixture Wall Actuator (MBFW)

Compliances & Certifications

- ADA Compliant
- BAA Compliant
- UL Certified
- UPC Certified
- cUPC Certified
- WaterSense Listed

NOTES

For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.



DESCRIPTION

PWT™ Concealed Solenoid (less sensor) Water Closet PWT Flushometer

FEATURES

- 1.28 gpf models and 1.6/2.4/3.5 gpf models
- Program set to 2 activations in 5 minutes with lockout
- Program is field changeable to 15, 30, 45 and 60 minute lockout times, or dorm setting
- Can be used with stainless-steel water closet fixtures from Acorn®, Bradley®, Metcraft® and other manufacturers
- PERMEX® Synthetic Rubber Diaphragm with Dual Filtered Fixed Bypass
- Single Flush
- Solenoid operated
- Includes standard or LED touch button for operation
- Stainless steel, vandal proof button, chemical resistant button operation designed with non-hold-open feature to keep fixture from surpassing intended water consumption
- XX' Connector cable has white arrows for easy alignment
- Hardwire power with battery backup
- 18" power cable for connection
- Use with EAF-11 plug-in transformer
- Up to 8 valve connections per EAF-11
- Four (4) Size AA Batteries
- Low Battery flashing LED
- **Retrofit Kit for**
- **Manual flushometers:**
 - Royal 603
 - Royal 611
 - Royal 613

- **Hydraulic flushometers:**

- Royal 9603
- Royal 9611
- Royal 9613

- **Can convert other vendor's valves with addition of 3325524 EBV31A Retrofit Kit Coupling Ring**

DOWNLOADS

- [8603-ESM Retrofit Installation Instructions](#)
- [8603-ESM Maintenance Guide](#)
- [Additional Downloads](#)