

OPTIONS**Flush Volume**

1.28 gpf (4.8 Lpf) (1.28)

1.6 gpf (6.0 Lpf) (1.6)

Finish

Brushed Stainless (SF)

Brushed Nickel (BN)

Graphite (GR)

Polished Brass (PB)

Polished Chrome (CP)

Power Type

Battery with Hardwired Option

Bypass

Filtered

Override

Electrical

Control Stop

Integrated

Outlet Tube

Adjustable Flush Connection

Compliances & Certifications

ADA Compliant

BAA Compliant

cUPC Certified

EPD

HPD

LEED Materials & Resources EPD Credit

LEED Materials & Resources HPD Credit

WaterSense Listed

BABAA Compliant

WELL Building Standard

NOTESFor product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.



Image for a standard CX 8154 shown

DESCRIPTION

CX Concealed Sensor Floor-mounted Water Closet Flushometer

FEATURES

- Fixed volume piston with filtered O-ring bypass
- Front access wall plate requires no rear access plumbing chase
- Sensor activated, hands-free operation
- Battery operated with hardwired option
- Electronic override button
- Low battery indicator light
- Vandal resistant wall plate
- Adjustable flush connection
- 8 1/2"(W) x 9 1/4"(H) Wall Box Panel Dimension

DOWNLOADS

- [CX 8158/8198 Installation Instructions](#)
- [CX 8158/8198 Repair and Maintenance Guide](#)
- [Additional Downloads](#)

VIDEOS

- ▶ CX Flushometer Product Video
- ▶ CX Flushometer - Sensor Installation
- ▶ CX Flushometer - Sensor Vacuum Service
- ▶ CX Flushometer - Sensor Piston Service
- ▶ CX Flushometer Product Video (Spanish)
- ▶ PVD Special Finishes

Sloan 10500 Seymour Ave, Franklin Park, IL 60131

Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com