



Sloan® Sensor Flushometer

SLOAN 111 ESS TMO

Product description

Sloan® Exposed Sensor Hardwired Water Closet Flushometer.

Compliances & Certifications



(BREEAM Water Credit, Green Globes Water, LEED Water, Satisfies LEED Credits)

Listed compliances and certifications may vary based on product variation.

Finish



Available in Polished Chrome (CP).

Connectivity

Downloads

- [Sloan_Regal ESS TMO Installation Instructions](#)
- [Optima ESS TMO Concealed Repair and Maintenance Guide](#)
- [Control Stop Repair and Maintenance Guide](#)
- [Additional Downloads](#)

Videos

- [ESS Flushometer](#)

Features

- Flush volumes start as low as 1.1 gpf/4.2 Lpf
- Water conservation is aided by a non-hold open push button, which prevents toilet from exceeding intended flush volume
- Adjustable tailpiece to accommodate different height requirements
- Integrity of the product is maintained with the vandal-resistant stop cap
- Durability is facilitated with high copper, low zinc brass castings for dezincification resistance
- Valve shall be in compliance to the applicable sections of ASSE 1037
- High chloramine resistant PERMEX Synthetic Rubber Diaphragm with Linear Filtered Bypass and Vortex Cleansing Action
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass

Warranty

[View Warranty Information](#)

Notes

All information contained within this document subject to change without notice.