

OPTIONS**Power Type**

Hardwired

Body Type

Mid

Mounting

Deck

Power Supply

Plug Adapter (PLG)

Hardwired Less Transformer (HLT)

Box Transformer (BOX)

Sensor Type

Infrared

Flow Rate

0.5 gpm (1.9 Lpm) (0.5GPM)

1.5 gpm (5.7 Lpm) (1.5GPM)

Spray Type

Multi-Laminar (MLM)

Aerated (installed) or Laminar (in box)

Laminar (LAM)

Trim Plate

None

4" (102mm) (4)

8" (203mm) (8)

Finish

Polished Chrome (CP)

Brushed Nickel (BN)

Polished Brass (PB)

Brushed Stainless (SF)

Control Access

Above Deck

Mixer

Integrated Side Mixer (ISM)

Back-Check Tee (TEE)

Below Deck Thermostatic Mixing Valve (BDT)

Mixer Not Included

Below Deck Manual Mixing Valve (BDM)

Special Features

Drain Pop Up (DPU)

Carbon Offset (CO)



Image for a standard EFX-200 shown

DESCRIPTION

BASYS® Hardwired-Powered Deck-Mounted Mid Body

FEATURES

Commercial Grade, ADA Compliant, Electronic, Sensor-Activated, Die-Cast Metal Hand Washing Faucet with the following features:

- One tool service
- All wetted components to be stainless steel, engineered thermoplastic, EPDM, and copper or copper alloy
- Solenoid housed in removable carrier that includes supply strainer
- Integral water supply shut off
- Supply strainer serviceable from above deck
- Vandal resistant spray insert, key housed inside faucet body
- All electronics sealed to IP-67
- Gold plated electrical contacts
- Above deck individual diagnostic indicators for battery life, solenoid condition, and power up mode
- Flexible, high pressure supply hoses, 3/8" compression connections
- Bi-stable magnetic solenoid
- Double infrared sensors with automatic setting feature
- Single hole installation
- Includes all mounting hardware
- Line purge mode, eliminates stagnant water
- Adjustable time-outs
- 3 year limited warranty

DOWNLOADS

- [EFX 1Xx/2Xx Installation Instructions](#)

Sloan 10500 Seymour Ave, Franklin Park, IL 60131

Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com

Compliances & Certifications

ADA Compliant
ASME A112.18.1 Compliant
CEC Compliant
EPD
HPD
Proposition 65
TAS
UPC Certified
UPC Low Lead Compliant
WELL Building Standard

NOTES

For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.

[Find a matching soap dispenser](#) for this faucet.

[Find a compatible sink](#) for this faucet.

- [EFX 1Xx/2Xx \(SP\) Installation Instructions](#)
- [EFX 1Xx/2Xx Caddy Replacement Installation Instructions](#)
- [Trim Plate Guide](#)
- [IR FAQs Repair and Maintenance Guide](#)
- [IR FAQs SP Repair and Maintenance Guide](#)
- [EFX-2XX Repair and Maintenance Guide](#)
- [Faucet Spray Heads Repair and Maintenance Guide](#)
- [Additional Downloads](#)

VIDEOS

-  [BASYS® Faucet Installation and Features](#)
-  [BASYS® Faucet Installation Mid Height Model](#)
-  [Sloan Connect App®](#)