

OPTIONS

Flush Volume

3.5 gpf (13.2 Lpf) (3.5)

1.6 gpf (6.0 Lpf) (1.6)

1.28 gpf (4.8 Lpf) (1.28)

Water Efficiency

Water Saver

Low Consumption

High Efficiency

L Dimension

3 3/4" (95mm) (3-3/4-LDIM)

10 3/4" (273mm) (10-3/4-LDIM)

6 3/4" (171mm) (6-3/4-LDIM)

4 3/4" (121mm) (4-3/4-LDIM)

8 3/4" (222mm) (8-3/4-LDIM)

2 ³/₄" (70mm) (2-3/4-LDIM)

7 ³/₄" (197mm) (7-3/4-LDIM)

9 ³/₄" (248mm) (9-3/4-LDIM)

14 3/4" (375mm) (14-3/4-LDIM)

5 3/4" (146mm) (5-3/4-LDIM)

Wall Box

Standard (not included, order separately)

Push Button

Metal Index (L)

3" Metal Oscillating (L3)

Control Stop

1" Straight (E)

Compliances & Certifications

BAA Compliant

BABAA Compliant

Made in the USA

UPC Certified

ADA Compliant

cUPC Certified

BREEAM Water Credit

Green Globes Water Credit

LEED V4 Water Efficiency Credit

Satisfies LEED Credits

NOTES

For product line drawings, view model-specific spec sheets.

All information contained within this document subject to change without notice.



DESCRIPTION

Royal® Concealed Manual Water Closet Flushometer

FEATURES

- Flush volumes start as low as 1.28 gpf/4.8 Lpf
- Water conservation is aided by the ADA-compliant, non-holdopen handle, which prevents toilet from exceeding intended flush volume
- Flush accuracy is controlled by CID™ technology, also enhancing water efficiency
- Integrity of the product is maintained with the vandalresistant stop cap
- Durability is facilitated with high copper, low zinc brass castings for dezincification resistance
- Adjustable tailpiece
- PERMEX synthetic rubber diaphragm with Dual Filtered Fixed Bypass
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

DOWNLOADS

- Sloan Concealed Installation Instructions
- Control Stop Repair and Maintenance Guide
- Flush Connections Flanges Repair and Maintenance Guide
- Tail Piece Repair and Maintenance Guide
- Concealed Flushometers Repair and Maintenance Guide
- Additional Downloads

Sloan 10500 Seymour Ave, Franklin Park, IL 60131

Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com