



ECOS® Sensor Flushometer

ECOS 111

Product description

ECOS® Exposed Sensor Hardwired Water Closet Flushometer.

Compliances & Certifications






















Listed compliances and certifications may vary based on product variation.

Finish







Available in Polished Chrome (CP), Graphite (GR), Brushed Stainless (SF), Brushed Nickel (BN).

Downloads

- Sloan ECOS Single_Dual-Flush Flushometer & Retrofit Valve Installation Instructions
- ECOS HW Repair and Maintenance Guide
- Ontrol Stop Repair and Maintenance Guide
- Additional Downloads

Videos

Sloan – Company Overview

Product Information ECOS 117

Features

- Employs an infrared sensor with multiple-focused, lobular sensing fields for high and low target detection
- · User-friendly, three-second flush delay
- High copper, low zinc brass castings for dezincification resistance
- Fixed metering bypass and no external volume adjustment to ensure water conservation
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037

Warranty

View Warranty Information

Notes

All information contained within this document subject to change without notice.



Featured projects



PLATFORM Night Club

Des Moines, IA

View project >

