

OPTIONS**Flush Volume**

3.5 gpf (13.2 Lpf) (3.5)

1.6 gpf (6.0 Lpf) (1.6)

Water Efficiency

Water Saver

Low Consumption

L Dimension

6 ¾" (171mm) (6-3/4-LDIM)

8 ¾" (222mm) (8-3/4-LDIM)

10 ¾" (273mm) (10-3/4-LDIM)

12 ¾" (324mm) (12-3/4-LDIM)

14 ¾" (375mm) (14-3/4-LDIM)

5 ¾" (146mm) (5-3/4-LDIM)

7 ¾" (197mm) (7-3/4-LDIM)

Wall Box

Standard (not included, order separately)

Push Button

3" Metal Oscillating (L3)

Metal Index (L)

Control Stop

1" Straight (E)

Ground Joint (GJ)

Special Features

Whitworth Thread (WWT)

Compliances & Certifications

BAA Compliant

BABAA Compliant

ADA Compliant

UPC Certified

NOTESFor product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.



Image for a standard NAVAL 143 shown

DESCRIPTION

Naval Concealed Manual Water Closet Flushometer

FEATURES

- Non-hold-open oscillating handle, Bak-Chek™ control stop and self-cleaning Xpelor Metering By-Pass ensure reliable operation and accurate flush delivery
- Available with adjustable or ground joint supply stop (ground joint recommended for salt water applications)
- Factory set flush volume of either 1.6 gpf/6.0 Lpf or 3.5 gpf/13.2 Lpf with adjustment range of 1.5 gpf/5.7 Lpf to 7.0 gpf/26.5 Lpf
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

DOWNLOADS

- [Naval Piston Type Exposed Installation Instructions](#)
- [Control Stop Repair and Maintenance Guide](#)
- [Flush Connections Flanges Repair and Maintenance Guide](#)
- [Tail Piece Repair and Maintenance Guide](#)
- [Concealed Flushometers Repair and Maintenance Guide](#)
- [Naval Repair and Maintenance Guide](#)
- [Additional Downloads](#)