



Naval Manual Flushometer

NAVAL 150-3.5-RB-3-3/4-LDIM-WWT

Product description

3.5 gpf, Rough Brass Finish, Fixture Connection Not Included, Single Flush, 3.75" L Dimension, Whitworth Thread, Naval Concealed Manual Water Closet Flushometer.

Compliances & Certifications



(BAA Compliant, IAPMO, UPC Certified)

Code 3141500

Finish

 Rough Brass (RB)

Downloads

- [Naval Piston Type Exposed Installation Instructions.pdf](#)
- [Naval Repair and Maintenance Guide.pdf](#)
- [Control Stop Repair and Maintenance Guide.pdf](#)
- [Additional Downloads](#)

Videos

- [Sloan - Company Overview](#)

Product Information

Details

- Flush Volume: 3.5 gpf (13.2 lpf)
 - Finish: Rough Brass (RB)
 - Valve: Piston
 - Valve Body Material: Red Brass
 - Fixture Type: Water Closet
 - Fixture Connection: Not Included
 - Rough-in Dimension: 24" (610mm)
 - Supply Pipe: 1" (25mm)
 - L Dimension: 3.75" (95mm) (3-3/4-LDIM)
 - Special Features 1: Whitworth Thread (WWT)
-

Features

- Non-hold-open oscillating handle, Bak-Chek™ control stop and self-cleaning Xpelor Metering By-Pass ensure reliable operation and accurate flush delivery
- Available with adjustable or ground joint supply stop (ground joint recommended for salt water applications)
- Factory set flush volume of either 1.6 gpf/6.0 Lpf or 3.5 gpf/13.2 Lpf with adjustment range of 1.5 gpf/5.7 Lpf to 7.0 gpf/26.5 Lpf
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037

NAVAL 150-3.5-RB-3-3/4-LDIM-WWT

Recommended specifications

Valve Body, Cover, Tailpiece and Control Stop shall be in conformance with ASTM Alloy Classification for Semi-Red Brass. Valve shall be in compliance with the applicable sections of ASSE 1037 and ANSI/ASME 112.19.2.

Valve Operating Pressure (Flowing)

15-80 psi (103 - 552 kPa). Specific fixtures may require greater minimum flowing pressure - consult manufacturer requirements.

Warranty

[View Warranty Information](#)

Notes

All information contained within this document subject to change without notice.

Looking for other variations of the NAVAL 150 product? [View the general spec sheet with all options.](#)

[Find a compatible urinal](#) for this flushometer.

[Find a compatible water closet](#) for this flushometer.

