

**OPTIONS****Flush Volume**

- 1.28 gpf (4.8 Lpf) (1.28)
- 1.6 gpf (6.0 Lpf) (1.6)
- 3.5 gpf (13.2 Lpf) (3.5)

**Water Efficiency**

- High Efficiency
- Low Consumption
- Water Saver

**Outlet Tube**

- Trap Primer (TP)

**Bumper**

- Angle Stop Extended (YG)

**Compliances & Certifications**

- ADA Compliant
- BAA Compliant
- BABAA Compliant
- Made in the USA
- cUPC Certified
- EPD
- HPD
- Satisfies LEED Credits
- UPC Certified
- WaterSense Listed

**NOTES**

For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.



Image for a standard GEM-2 113 shown

**DESCRIPTION**

GEM-2® Exposed Manual Water Closet Flushometer

**FEATURES**

- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

**DOWNLOADS**

- [GEM/GEM 2 Piston Type Exposed Installation Instructions](#)
- [Control Stop Repair and Maintenance Guide](#)
- [Flush Connections Flanges Repair and Maintenance Guide](#)
- [Tail Piece Repair and Maintenance Guide](#)
- [Gem 2 Repair and Maintenance Guide](#)
- [Additional Downloads](#)