

**OPTIONS****Flush Volume**

- 1.28 gpf (4.8 Lpf) (1.28)
- 1.6/1.1 gpf (6.0/4.2 Lpf) (1.6/1.1)

**Compliances & Certifications**

- ADA Compliant
- BAA Compliant
- BABAA Compliant
- BREEAM Water Credit
- Green Globes Water Credit
- cUPC Certified
- cUPC Green Certified
- LEED V4 Water Efficiency Credit
- Satisfies LEED Credits
- WaterSense Listed

**NOTES**

For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.



Image for a standard ECOS 115 shown

**DESCRIPTION**

ECOS® Exposed Sensor Hardwired Water Closet Flushometer

**FEATURES**

- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

**DOWNLOADS**

- [Sloan ECOS Single/Dual-Flush Flushometer & Retrofit Valve Installation Instructions](#)
- [ECOS HW Repair and Maintenance Guide](#)
- [Control Stop Repair and Maintenance Guide](#)
- [Flush Connections Flanges Repair and Maintenance Guide](#)
- [Tail Piece Repair and Maintenance Guide](#)
- [ECOS Repair and Maintenance Guide](#)
- [Additional Downloads](#)

Sloan 10500 Seymour Ave, Franklin Park, IL 60131

Phone: 800.982.5839 • Fax: 800.447.8329 • [sloan.com](http://sloan.com)