



Water Closet & Flushometer Combo

WETS-2010.1030

Product description

Standard, ST-2010 Water Closet and ROYAL 940 Flushometer.

Compliances & Certifications



(BREEAM Water Credit, EPD, Green Globes Water, HPD, LEED Water, Satisfies LEED Credits, WELL Building Standard)

Code 20101030

Downloads

- [Royal_Regal Series 900 Hydraulic Installation Instructions.pdf](#)
- [HET Rear Spud Installation Instructions.pdf](#)
- [SS:ST:SU:WETS:WEUS Fixtures Repair and Maintenance Guide.pdf](#)
- [Fixture Brochure.pdf](#)
- [Additional Downloads](#)

Videos

- [Sloan – Company Overview](#)

Details

- Flush Volume: 1.28 gpf (4.8 lpf)

Features

- Various types of push-button flush actuators, which can be remotely positioned
- Flush volumes start as low as 1.6 gpf/6.0 Lpf
- Water conservation is aided by the ADA-compliant, non-hold-open
- Vandal-resistant stop cap to facilitate security
- Made from rough brass
- PERMEX® Synthetic Rubber Diaphragm with Dual Filtered Fixed Bypass
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037
- Durable, hygienic vitreous china construction with elongated rim
- IAPMO certified to meet or exceed ASME A112.19.2 standards

Components

- Flushometer: Code 3913407

Warranty

[View Warranty Information](#)

Notes

All information contained within this document subject to change without notice.

Static load tested according to the procedure outlined in Section 6.7 of ASME A112.19.2. Not recommended for bariatric use.

