

OPTIONS
Flush Volume

- 0.5 gpf (1.9 Lpf) (0.5)
- 1.0/1.5 gpf (3.8/5.7 Lpf) (1.0/1.5)
- 0.125 gpf (0.5 Lpf) (0.125)
- 0.25 gpf (0.9 Lpf) (0.25)

Finish

- Polished Chrome (CP)

Power Type

- Solar

Activation

- Sensor

Valve

- Diaphragm

Water Efficiency

- High Efficiency

Fixture Type

- Urinal

Fixture Connection

- Top Spud

Installation

- Exposed

Override

- Electrical

Handle

- Less Handle Body (LH)

Control Stop

- Adjustable Ground Joint for Tek (XDT)

Special Features

- Fits †Zurn® valve bodies (Z)

Specialty

- Retrofit

Compliances & Certifications

- ADA Compliant
- BREEAM Water Credit
- Green Globes Water Credit
- Satisfies LEED Credits
- cUPC Certified
- cUPC Green Certified



Image for a standard SOLIS RESS-U shown

DESCRIPTION

SOLIS® Exposed Sensor Urinal Retrofit Flushometer

FEATURES

- Quiet, Exposed, SOLIS®, Solar Powered, Sensor Activated Urinal Flushometer Retrofit Conversion Kit for Royal®, Sloan® and Regal®
- User friendly three (3) second Flush Delay
- “Low Battery” Flashing LED
- Solar Powered. The sensor assembly is powered by a solar cell that will harvest power from the artificial indoor light (incandescent, fluorescent or LED), and use it as the energy source. The solar cell can provide approximately 100% power with 650 illuminance (lux).
- Four (4) Size AA Battery Back-up Power Source
- Infrared Sensor with Multiple-focused, Lobular Sensing Fields for high and low target detection
- Fixed Metering Bypass and No External Volume Adjustment to Ensure Water Conservation
- PERMEX® Synthetic Rubber Flex Tube Diaphragm with twin linear filtered bypass and vortex cleansing action
- Flex Tube Diaphragm designed for improved life and reduced maintenance
- ADA Compliant Sloan Solis® Solar Powered Infrared Sensor for automatic “No Hands” operation
- Diaphragm molded from PERMEX® Rubber Compound for Chloramine resistance
- Courtesy Flush® Override Button

DOWNLOADS

- [Control Stop Repair and Maintenance Guide](#)
- [Flush Connections Flanges Repair and Maintenance Guide](#)

Sloan 10500 Seymour Ave, Franklin Park, IL 60131

Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com

BAA Compliant

NOTES

For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.

† The brands and/or products names referenced herein may be subject to trademark rights of their respective owners. Use of the brands and names is for identification purposes only and does not imply affiliation with or endorsement by Sloan.

- [Tail Piece Repair and Maintenance Guide](#)
- [Exposed Solis Repair and Maintenance Guide](#)
- [Additional Downloads](#)