



## Sloan Optima Air® Hand Dryer

EHD-701-BN

### Product description

EHD-701, 110/120V, Sloan Optima Air® Sensor-Operated Wall-Mounted - ADA Hand Dryer.

### Compliances & Certifications



(BAA Compliant, EPD, UL Certified (US and Canada), WELL Building Standard)

Code 3366129

### Finish



Brushed Nickel (BN)

### Downloads

- [OPTIMA AIR HAND DRYER EHD-700 SERIES. pdf](#)
- [Sloan Hand Dryers Brochure.pdf](#)
- [Additional Downloads](#)

### Videos

- [Sloan – Company Overview](#)

---

## Details

- Finish: Brushed Nickel (BN)
- Voltage: 110/120V
- Wattage: 1000 Watts
- Amperage: 7.0A-7.7A
- Mounting: Wall-Mounted - ADA
- Power Type: Hardwired
- Depth: 13.93" (102mm)
- Height: 13.93" (354mm)
- Width: 9.156" (233mm)

---

## Features

- Hygienic hand drying solution, 14 second dry time
- Electric Specifications: 110-120V – 7-7.7 Amps, 770-915 Watts, 50/60 Hz, Can install multiple units on one circuit
- Meets ADA requirements without the need of a recess kit
- Adjustable speed and sound (High-Low), Adjustable Heat (High-Low-Off)
- 95% cost savings vs. paper towels
- Weight: 8-10 lbs.
- Vandal resistant cover design, Virtually maintenance free
- Suggested Mounting Heights for Ideal Performance (from floor to bottom of dryer): Men: 45" (114 cm), Women: 43" (109 cm), Teenagers: 41" (104 cm), Children: 35" (89 cm), ADA: 37" (94 cm).  
Note: When mounting for any user ensure that it is mounted below the 48" ADA Maximum
- Externally visible Red LED light that flashes error codes to assist in troubleshooting and identify if filter has been clogged
- Air temperature of up to 141°F (61°C) at a 72°F (22°C) ambient room temperature at the hands (4 inches [102 mm] below air outlet).
- 35-second lockout feature if hands are not removed

---

## Recommended specifications

Sloan Optima Air® Sensor Operated ADA Hand Dryer. 120V/110V Brushed Nickel Finish.

---

## Warranty

[View Warranty Information](#)

---

## Notes

All information contained within this document subject to change without notice.

