



Elongated Floor-Mounted Standard Gravity Toilet

WETS-4009.4111-STG

Product description

SloanTec® Glaze, Floor-Mounted 1.1 gpf (4.2 lpf)
Standard 12" Rough-in Right Handle.

Compliances & Certifications



(BAA Compliant, CalGreen Compliant, CEC Compliant, cUPC Certified, cUPC Green Certified, NOM Certified, EPA WaterSense Listed)

Code WETS-4009.4111-STG

Downloads

- [WETS 4000 Series Installation Instructions.pdf](#)
- [Sloan Gravity Toilets Brochure.pdf](#)
- [Additional Downloads](#)

Videos

- [Sloan – Company Overview](#)

Details

- Flush Volume: 1.1 gpf (4.2 lpf)
- Handle Side: Right

Features

- Permanent SloanTec® hydrophobic antimicrobial glaze inhibits the growth and buildup of germs, bacteria, mold, mildew and mineral scale on the surfaces

Components

- Bowl: Code 2174009
- Tank: Code 21740096

Recommended Seats

- Bemis - 1955CT/1955SSCT & 2155CT/2155SSCT
- Church - 295CT/295SSCT & 2155CT/2155SSCT
- Church - 1580CT

Plumbing System Requirements

- Maximum Static Pressure: 80 PSI (552 kPa)
- Minimum Static Pressure: 20 PSI (138 kPa)

Warranty

[View Warranty Information](#)

Notes

All information contained within this document subject to change without notice.

All vitreous china dimensions shown in these drawings are nominal and not to scale. Dimensions can vary within the tolerances established in the governing ASME A112.19.2/CSA B45.1 standard. It is important to consider this when planning rough-in and plumbing layouts.

Static load tested according to the procedure outlined in Section 6.7 of ASME A112.19.2. Not recommended for bariatric use. WaterSense compliant when used with a WaterSense compliant flushometer.

