



BASYS® Sensor Faucet

EFX-280-TUR-TEE-CP-0.5GPM-MLM-FCT

Product description

Turbine Power Supply, Back-Check Tee, Polished Chrome Finish, 0.5 gpm, Multi-Laminar Spray, Infrared Sensor, BASYS® Turbine-Powered Deck-Mounted Mid Body Faucet.

Compliances & Certifications



(ADA Compliant*, ASME A112.18.1 Compliant, BREEAM Materials Credit, BREEAM Water Credit, CalGreen Compliant, CEC Compliant, EPD, Green Globes Credit, Green Globes Water, HPD, IAPMO, LEED Credit, LEED HPD, NYC604.4, Satisfies LEED Credits, TAS, UPC Low Lead Certified, WELL Building Standard)

Code 3324371

Finish

 Polished Chrome (CP)

Downloads

-  EFX 1Xx_2Xx (SP) Installation Instructions.pdf
-  EFX 1Xx_2Xx Installation Instructions.pdf
-  EFX-2XX Repair and Maintenance Guide.pdf
-  Trim Plate Guide.pdf
-  Sloan BASYS Brochure.pdf
-  Additional Downloads

Videos

-  Sloan Connect App®
-  BASYS® Faucet Installation and Features
-  BASYS® Faucet Installation Mid Height Model

Details

- Flow Rate: 0.5 gpm (1.9 Lpm) (0.5GPM)
- Spray Type: Multi-Laminar (MLM)
- Sensor Type: Infrared
- Mounting Type: Single Hole
- Power Supply: Turbine (TUR)
- Temperature Mixer: Back-Check Tee (TEE)
- Finish: Polished Chrome (CP)
- Factory Default Timeout: 10s
- Factory Default GPC: 0.083 gpc

Features

Commercial Grade, ADA Compliant, Electronic, Sensor-Activated, Die-Cast Metal Hand Washing Faucet with the following features:

- One tool service
- All wetted components to be stainless steel, engineered thermoplastic, EPDM, and copper or copper alloy
- Solenoid housed in removable carrier that includes supply strainer
- Integral water supply shut off
- Supply strainer serviceable from above deck
- Vandal resistant spray insert, key housed inside faucet body
- All electronics sealed to IP-67
- Gold plated electrical contacts
- Above deck individual diagnostic indicators for battery life, solenoid condition, and power-up mode
- Flexible, high pressure supply hoses, 3/8" compression connections
- Bi-stable magnetic solenoid
- Four (4) "AA" alkaline batteries
- Double infrared sensors with automatic setting feature
- Single hole installation
- Includes all mounting hardware
- Line purge mode, eliminates stagnant water
- Adjustable time-outs
- 3 year limited warranty
- Chrome plated finish

Recommended specifications

Sloan BASYS Model No. EFX-280-TUR-CP-0.5GPM-MLM-IR-FCT Infrared Sensor Activated Electronic Handwashing Faucet for pretempered or hot/cold water supplies. Product to have double infrared sensors with automatic setting feature. Solenoid valve housed in removable carrier that closes water supply upon removal eliminating, need to access control stops. Solenoid carrier includes strainer for easy above deck service. Thermostatic mixer ordered separately to comply with ASSE 1070 requirements. The product shall be tested and certified to industry standards: ASME A112.18.1M, CSA B125.1, California Health and Safety Code 116875

Electrical specifications

- Battery Life: 8 years 8,000 cycles/month
- Sensor Range: 4"-5" (102-127 mm)

Warranty

[View Warranty Information](#)


Notes

All information contained within this document subject to change without notice.

*Compliant with ADA accessibility requirements when installed according to ADA standards.

Looking for other variations of the EFX-280 product? [View the general spec sheet with all options.](#)
[Find a matching soap dispenser](#) for this faucet.
[Find a compatible sink](#) for this faucet

EFX-280.00X.0X0X Faucet
with Single Line Water Supply



EFX-280.50X.0X0X Faucet
with Hot & Cold Water Supply

