



Sloan® Sensor Flushometer

SLOAN 197 ESS-0.125-RB-TMO-SWB-24V

Product description

0.125 gpf, Dual-Filtered Bypass, Rough Brass Finish, Fixture Connection Top Spud, Single Flush, 2"-10.75" L Dimension, True Mechanical Override, Hardwired, Sensor-Operated, 24V, Small Wall Box Included Wall Box, Sloan® Concealed Sensor Hardwired Urinal Flushometer.

Compliances & Certifications



(ADA Compliant, BAA Compliant, BABAA Compliant, cULus Certified)

Code 3773227

Finish



Rough Brass (RB)

Downloads

- [Sloan 152_140_153_195 ESS TMO SWB Installation Instructions.pdf](#)
- [Sloan_Regal Concealed and Exposed Sensor Installation Instructions.pdf](#)
- [Flush Connections Flanges Repair and Maintenance Guide.pdf](#)
- [Tail Piece Repair and Maintenance Guide.pdf](#)
- [Optima ESS Repair and Maintenance Guide.pdf](#)
- [Retrofits Brochure.pdf](#)
- [Additional Downloads](#)

Videos

- [ESS Flushometer](#)

Details

- Flush Volume: 0.125 gpf (0.5 lpf)
- Finish: Rough Brass (RB)
- Power Type: Hardwired
- Valve: Diaphragm
- Bypass: Dual-Filtered Bypass
- Valve Body Material: Semi-red Brass
- Fixture Type: Urinal
- Fixture Connection: Top Spud
- Rough-in Dimension: 13.5" (343mm)
- Spud Coupling: 0.75" (19mm)
- Supply Pipe: 0.75" (19mm)
- L Dimension: 2"-10.75" (51-273mm)
- Override: True Mechanical (TMO)
- Wall Box: Small Wall Box Included (SWB)
- Voltage: 24V (24V)

Features

- Sensor-activated, hardwired urinal flushometer
- High Chloramine Resistant PERMEX® Synthetic Rubber Diaphragm with Linear Filtered Bypass and Vortex Cleansing Action
- Durability is facilitated with high copper, low zinc brass castings for dezincification resistance
- Adjustable tailpiece
- High chloramine resistant PERMEX® Synthetic Rubber Diaphragm with Linear Filtered Bypass and Vortex Cleansing Action
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037

Recommended specifications

Valve Body, Cover, Tailpiece and Control Stop shall be in conformance with ASTM Alloy Classification for Semi-Red Brass. Valve shall be in compliance with the applicable sections of ASSE 1037 and ANSI/ASME 112.19.2.

Electrical specifications

- Arming Delay: 8 seconds
- Control Circuit:
 - Solid State
 - 24 VAC Input
 - 24 VAC Output
- Flush Delay: 1 seconds
- Sensor Range: 15"-30" (381 - 762mm)
- Self-Adaptive Window: ±8"
- Solenoid Operator: 24 VAC
- Transformers (Specify Separately):
 - EL-154/0345154
 - EL-342/0345999

Valve Operating Pressure (Flowing)

15-80 psi (103 - 552 kPa). Specific fixtures may require greater minimum flowing pressure - consult manufacturer requirements.

Warranty

[View Warranty Information](#)

Notes

All information contained within this document subject to change without notice.

Looking for other variations of the SLOAN 197 ESS product?
[View the general spec sheet with all options.](#)

[Find a compatible urinal](#) for this flushometer.
[Find a compatible water closet](#) for this flushometer.

