



Elongated Floor-Mounted Standard Pressure Assist Water Closet

WETS-8009.8113

Product description

Standard, Floor-Mounted 1.6 gpf (6 lpf) Standard 12" Rough-in Right Handle.

Compliances & Certifications



(BAA Compliant, IAPMO, IAPMO Mexico, NOM Certified, cUPC Certified)

Code 80098113

Downloads

- [Pressure-Assisted Toilets Installation Instructions.pdf](#)
- [Flushmate Owner's Manual.pdf](#)
- [Pressure-Assisted Toilets Repair and Maintenance Guide.pdf](#)
- [Pressure-Assisted Toilets Brochure.pdf](#)
- [Fixture Brochure.pdf](#)
- [Additional Downloads](#)

Videos

- [Sloan - Company Overview](#)

Details

- Flush Volume: 1.6 gpf (6 lpf)
- Handle Side: Right

Features

- White Vitreous China
- Elongated bowl
- Floor mounted, floor outlet
- 12" (305mm) rough-in
- Chrome metal flush handle
- Secure, anti-rocking 3-point tank mounting system
- Powered by Flushmate® brand pressure-assist flushing technology to achieve 900g MaP score
- Over 60 ft (18.3 m) drainline carry performance
- Water spot area: 11 ¼ x 9 ¾ (286 mm x 248 mm)
- Smooth, quiet cable activated flush handle - right hand
- Fully glazed trapway
- Closet bolts and caps included
- Toilet seat and wax ring not included
- Tank and bowl are packed in a single carton

Components

- Bowl: Code 2108009
- Tank: Code 2108113

Recommended Seats

- Bemis - 1955CT/1955SSCT & 2155CT/2155SSCT
- Church - 295CT/295SSCT & 2155CT/2155SSCT

Warranty

[View Warranty Information](#)

Notes

All information contained within this document subject to change without notice.

Static load tested according to the procedure outlined in Section 6.7 of ASME A112.19.2. Not recommended for bariatric use. @AttributePlainHyperlinks:Find a compatible flushometer for this water closet

All vitreous china dimensions shown in these drawings are nominal and not to scale. Dimensions can vary within the tolerances established in the governing ASME A112.19.2/CSA B45.1 standard. It is important to consider this when planning rough-in and plumbing layouts.

