

OPTIONS

Flush Volume

1.6/1.1 gpf (6.0/4.2 Lpf) (1.6/1.1)
1.28 gpf (4.8 Lpf) (1.28)

Power Type

Battery
Hardwired (HW)

Override

Electrical

Handle

Saniguard®

Control Stop

1"

Inlet

1"

Compliances & Certifications

ADA Compliant
BAA Compliant
BABAA Compliant
BREEAM Water Credit
Green Globes Water Credit
cUPC Certified
cUPC Green Certified
LEED V4 Water Efficiency Credit
Satisfies LEED Credits
UPC Certified

NOTES

For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.



DESCRIPTION

ECOS® Exposed Sensor Specialty Water Closet Bedpan Washer Flushometer

FEATURES

- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

DOWNLOADS

- [BPW Exposed Installation Instructions](#)
- [Sloan ECOS Single/Dual-Flush Flushometer & Retrofit Valve Installation Instructions](#)
- [Control Stop Repair and Maintenance Guide](#)
- [Flush Connections Flanges Repair and Maintenance Guide](#)
- [Tail Piece Repair and Maintenance Guide](#)
- [ECOS Repair and Maintenance Guide](#)
- [Slimline Bedpan Washer Repair and Maintenance Guide](#)
- [Additional Downloads](#)