



Variation Not Shown: Dual Flush

Sloan® Manual Flushometer

SLOAN WES 111-1.6-CP-LL

Product description

1.6 gpf, Polished Chrome Finish, Fixture Connection Top Spud, Single Flush, Less Logo, Sloan® Exposed Manual Water Closet Flushometer.

Compliances & Certifications



(ADA Compliant*, BAA Compliant, cUPC Green Certified, IAPMO, Made in the USA)

Code 3720007

Finish

 Polished Chrome (CP)

Downloads

-  [UPPERCUT Installation Instructions.pdf](#)
-  [Control Stop Repair and Maintenance Guide.pdf](#)
-  [Flush Connections Flanges Repair and Maintenance Guide.pdf](#)
-  [Additional Downloads](#)

Videos

-  [Sloan - Company Overview](#)

Details

- Flush Volume: 1.6 gpf (6.0 lpf)
 - Finish: Polished Chrome (CP)
 - Valve: Diaphragm
 - Valve Body Material: Semi-red Brass
 - Fixture Type: Water Closet
 - Fixture Connection: Top Spud
 - Rough-in Dimension: 11.5" (292mm)
 - Spud Coupling: 1.5" (38mm)
 - Supply Pipe: 1" (25mm)
 - Special Features 1: Less Logo (LL)
-

Features

- High chloramine resistant PERMEX®synthetic rubber diaphragm with Linear Filtered Bypass and Vortex Cleansing Action
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037

Valve Operating Pressure (Flowing)

15-80 psi (103 - 552 kPa). Specific fixtures may require greater minimum flowing pressure - consult manufacturer requirements.

Warranty

[View Warranty Information](#)

Notes

All information contained within this document subject to change without notice.

*Compliant with ADA accessibility requirements when installed according to ADA standards.

Looking for other variations of the SLOAN WES 111 product?

[View the general spec sheet with all options.](#)

[Find a compatible urinal](#) for this flushometer.

[Find a compatible water closet](#) for this flushometer.

