

OPTIONS**Power Type**

Battery

Body Type

Low

Mounting

Deck

Power Supply

Battery (BAT)

Sensor Type

Infrared

Capacitance (CAP)

Flow Rate

0.5 gpm (1.9 Lpm) (0.5GPM)

1.5 gpm (5.7 Lpm) (1.5GPM)

Spray Type

Multi-Laminar (MLM)

Aerated (installed) or Laminar (in box)

Trim Plate

None

4" (102mm) (4)

8" (203mm) (8)

Finish

Polished Chrome (CP)

Control Access

Above Deck

Below Deck

Mixer

Back-Check Tee (TEE)

Below Deck Thermostatic Mixing Valve (BDT)

Below Deck Manual Mixing Valve (BDM)

Integrated Side Mixer (ISM)

Compliances & Certifications

ADA Compliant

ASME A112.18.1 Compliant

CEC Compliant

EPD

HPD

IAPMO

Proposition 65

TAS



Image for a standard EFX-350 shown

DESCRIPTION

BASYS® Battery-Powered Deck-Mounted Low Body

FEATURES

Commercial Grade, ADA Compliant, Electronic, Sensor-Activated, Die-Cast Metal Hand Washing Faucet with the following features:

- One tool service
- Solenoid housed in removable carrier that includes supply strainer
- Integral water supply shut off
- Vandal resistant spray insert, key housed inside faucet body
- All electronics sealed to IP-67
- Gold plated electrical contacts
- Above deck individual diagnostic indicators for battery life, solenoid condition, and power-up mode
- Flexible, high pressure supply hose, 3/8" compression connections
- Bi-stable magnetic solenoid
- Four (4) "AA" alkaline batteries
- Double infrared sensors with automatic setting feature
- Single hole installation (pedestal)
- Includes all mounting hardware
- 3 year limited warranty

DOWNLOADS

- [EFX 3Xx/6Xx Capacitance Installation Instructions](#)
- [EFX 3Xx/6Xx \(SP\) Installation Instructions](#)
- [EFX 3Xx/6Xx Active IR Installation Instructions](#)
- [EFX 3Xx/6Xx Active IR \(SP\) Installation Instructions](#)
- [Trim Plate Guide](#)

Sloan 10500 Seymour Ave, Franklin Park, IL 60131

Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com

UPC Certified

UPC Low Lead Compliant

NOTES

For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.

[Find a matching soap dispenser](#) for this faucet.

[Find a compatible sink](#) for this faucet.

- [IR FAQs Repair and Maintenance Guide](#)
- [IR FAQs SP Repair and Maintenance Guide](#)
- [EFX-3XX \(Capacitance\) Repair and Maintenance Guide](#)
- [EFX-3XX Repair and Maintenance Guide](#)
- [Faucet Spray Heads Repair and Maintenance Guide](#)
- [Additional Downloads](#)

VIDEOS

- ▶ [BASYS® Faucet Installation and Features](#)
- ▶ [BASYS® Faucet Installation Low Height Model](#)
- ▶ [Sloan Connect App®](#)

Sloan 10500 Seymour Ave, Franklin Park, IL 60131

Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com