



## G2 Sensor Flushometer

G2 8180-3.5-CP

### Product description

3.5 gpf, Polished Chrome Finish, Fixture Connection Top Spud, Single Flush, Battery, G2 Exposed Sensor Urinal Flushometer.

### Compliances & Certifications



(ADA Compliant\*, BAA Compliant, IAPMO, UL Certified (US), cUPC Certified)

Code 3250408

### Finish

 Polished Chrome (CP)

### Downloads

-  G2 and ECOS Single Flush Optima Plus Valve Installation Instructions duplicate.pdf
-  G2 Repair and Maintenance Guide.pdf
-  Control Stop Repair and Maintenance Guide.pdf
-  Additional Downloads

### Videos

-  Sloan - Company Overview

Details

- Flush Volume: 3.5 gpf (13.2 lpf)
- Finish: Polished Chrome (CP)
- Power Type: Battery
- Valve: Diaphragm
- Valve Body Material: Semi-red Brass
- Fixture Type: Urinal
- Fixture Connection: Top Spud
- Rough-in Dimension: 11.5" (292mm)
- Spud Coupling: 1.25" (32mm)
- Supply Pipe: 1" (25mm)

Features

- ADA-compliant flushometer automatically operates by means of a infrared sensor with multiple-focused, lobular sensing fields for high and low target detection
- Fixed metering bypass and no external volume adjustment to ensure water conservation
- Adjustable tailpiece to accommodate different height requirements
- High copper, low zinc brass castings for dezincification resistance
- Available in 0.5 gpf/1.9 Lpf, low consumption (1.0 gpf/3.8 Lpf), water saver (1.5 gpf/5.7 Lpf), and conventional (3.5 gpf/13.2 Lpf) models
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037

Recommended specifications

Valve Body, Cover, Tailpiece and Control Stop shall be in conformance with ASTM Alloy Classification for Semi-Red Brass. Valve shall be in compliance with the applicable sections of ASSE 1037 and ANSI/ASME 112.19.2.

Valve Operating Pressure (Flowing)

15-80 psi (103 - 552 kPa). Specific fixtures may require greater minimum flowing pressure - consult manufacturer requirements.

Battery Specifications

| Usage     | 4-AA Battery Service Life† |        |         |       |
|-----------|----------------------------|--------|---------|-------|
|           | 14.5 yrs                   | 12 yrs | 7.2 yrs | 6 yrs |
| per month | 500                        | 1,000  | 3,000   | 4,000 |
| per day   | 25                         | 50     | 150     | 200   |

† Service life varies according to actual usage and restroom conditions  
Battery shelf life: Alkaline= ~10 years - Lithium= ~25 years

Warranty

[View Warranty Information](#)

Notes

All information contained within this document subject to change without notice.

\*Compliant with ADA accessibility requirements when installed according to ADA standards.

Looking for other variations of the G2 8180 product? [View the general spec sheet with all options.](#)  
[Find a compatible urinal](#) for this flushometer.  
[Find a compatible water closet](#) for this flushometer.

