

Retrofit Sensor Flushometer

EBV89A-CP

Product description

Polished Chrome Finish, Fixture Connection Top Spud, Single Flush, Electrical Override, Battery, Infrared, Retrofit Exposed Sensor Urinal/Water Closet Flushometer.

Compliances & Certifications

BREEAM WATER

(BREEAM Water Credit, Green Globes Water)

Code 0325105

Finish

Polished Chrome (CP)

Downloads

- Side Mount Operator Unit Installation Instructions.pdf
- Side Mount Operator Unit Installation Instructions.pdf
- EBV-89A Side Mount Repair and Maintenance Guide.pdf
- Retrofits Brochure.pdf
- Additional Downloads

Videos

- Sloan – Company Overview

⚠ WARNING: Cancer and Reproductive Harm – www.P65Warnings.ca.gov

Sloan 10500 Seymour Ave, Franklin Park 800.982.5839 sloan.com

Details

- Finish: Polished Chrome (CP)
- Power Type: Battery
- Fixture Type: Urinal/Water Closet
- Fixture Connection: Top Spud
- Override: Electrical

Features

- Battery powered
- Estimated 3 year battery life

Electrical specifications

- Control Circuit:
  - Solid State
  - 6 VDC Input
  - 24 Hour Sentinel Flush
- Sensor Range: 22”-42” (559 - 1067mm)

Valve Operating Pressure (Flowing)

15-80 psi (103 - 552 kPa). Specific fixtures may require greater minimum flowing pressure - consult manufacturer requirements.

Warranty

View Warranty Information

Notes

All information contained within this document subject to change without notice.

Looking for other variations of the EBV89A product? View the general spec sheet with all options.
Find a compatible urinal for this flushometer.
Find a compatible water closet for this flushometer.

Side Mount Operator unit shown on an existing Sloan Regal
Model 110/111 Closet Flushometer

