

OPTIONS**Flush Volume**

- 1.1 gpf (4.2 Lpf) (1.1)
- 1.28 gpf (4.8 Lpf) (1.28)
- 1.6 gpf (6.0 Lpf) (1.6)

Finish

- Brushed Nickel (BN)
- Brushed Stainless (SF)
- Graphite (GR)
- Polished Brass (PB)
- Polished Chrome (CP)

Water Efficiency

- High Efficiency
- Low Consumption

Wall Box

- Front Accessible

Compliances & Certifications

- ADA Compliant
- BAA Compliant
- BABAA Compliant
- BREEAM Water Credit
- Green Globes Water Credit
- HPD
- LEED Materials & Resources HPD Credit
- cUPC Certified
- cUPC Green Certified
- EPD

NOTES

For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.



Image for a standard CX 158 shown

DESCRIPTION

CX Concealed Manual Water Closet Flushometer

FEATURES

- Fixed volume piston with filtered O-ring bypass
- Front access wall plate requires no rear access plumbing chase
- ADA compliant push button
- Vandal resistant wall plate
- Adjustable flush connection
- 8 1/2" (W) x 9 1/4" (H) Wall Box Panel Dimension

DOWNLOADS

- [CX 158/198 Installation Instructions](#)
- [CX 158/198 Repair and Maintenance Guide](#)
- [Additional Downloads](#)

VIDEOS

- ▶ [CX Flushometer Product Video](#)
- ▶ [CX Flushometer - Manual Installation](#)
- ▶ [CX Flushometer - Manual Vacuum Service](#)
- ▶ [CX Flushometer - Manual Piston Service](#)
- ▶ [CX Flushometer Product Video \(Spanish\)](#)
- ▶ [PVD Special Finishes](#)

Sloan 10500 Seymour Ave, Franklin Park, IL 60131

Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com