

OPTIONS**Flush Volume**

1.28 gpf (4.8 Lpf) (1.28)

1.6 gpf (6.0 Lpf) (1.6)

Water Efficiency

High Efficiency

Low Consumption

L Dimension

10 ¾" (273mm) (10-3/4-LDIM)

2 ¾" (70mm) (2-3/4-LDIM)

Wall Box

Standard (not included, order separately)

Push Button

Metal Index (L)

Control Stop

1" Straight (E)

Vacuum Breaker

11.5"

Compliances & Certifications

BAA Compliant

BABAA Compliant

Made in the USA

UPC Certified

cUPC Certified

BREEAM Water Credit

Green Globes Water Credit

LEED V4 Water Efficiency Credit

Satisfies LEED Credits

WaterSense Listed

NOTESFor product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.

**DESCRIPTION**

Crown® Concealed Manual Water Closet Flushometer

FEATURES

- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

DOWNLOADS

- [Crown Piston Type Exposed Installation Instructions](#)
- [Control Stop Repair and Maintenance Guide](#)
- [Flush Connections Flanges Repair and Maintenance Guide](#)
- [Tail Piece Repair and Maintenance Guide](#)
- [Crown/Crown II Repair and Maintenance Guide](#)
- [Concealed Flushometers Repair and Maintenance Guide](#)
- [Crown Piston Assembly Repair Kit](#)
- [Additional Downloads](#)

VIDEOS[Crown Piston Flushometer Basics](#)