



Royal® Sensor Flushometer

ROYAL 195 ESS

Product description

Royal® Concealed Sensor Hardwired Urinal Flushometer.

Compliances & Certifications






















Listed compliances and certifications may vary based on product variation.

Finish





Available in Graphite (GR), Brushed Stainless (SF).

Downloads

- Royal ESS Concealed and Exposed Installation
- Royal 152_195 ESS TMO (Spanish) Installation Instructions
- Royal 152_195 ESS TMO Installation Instructions
- Ontrol Stop Repair and Maintenance Guide
- Flush Connections Flanges Repair and Maintenance Guide
- Retrofits Brochure
- Additional Downloads

Videos

ESS Flushometer

Features

- · Flush volumes start as low as a pint of water
- Water conservation is aided by the ADA-compliant, non-holdopen handle, which prevents urinal from exceeding intended flush volume
- Flush accuracy is controlled by CID™ technology, also enhancing water efficiency
- Durability is facilitated with high copper, low zinc brass castings for dezincification resistance
- · Adjustable tailpiece
- PERMEX® Synthetic Rubber Diaphragm with Dual Filtered Fixed Bypass
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037

Warranty

View Warranty Information

Notes

All information contained within this document subject to change without notice.

