

OPTIONS

Flush Volume

- 1.6 gpf (6.0 Lpf) (1.6)
- 2.4 gpf (9.1 Lpf) (2.4)
- 1.28 gpf (4.8 Lpf) (1.28)

Compliances & Certifications

- BAA Compliant
- BABAA Compliant
- cUPC Certified
- UPC Certified
- ADA Compliant
- WaterSense Listed
- UL Certified

NOTES

For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.



DESCRIPTION

Sloan® Concealed Solenoid (less sensor) Water Closet PWT Flushometer

FEATURES

- Various flush volumes available to match with existing fixtures and meet water-efficiency goals
- Choose from Flushometers intended for use with stainless-steel water closet fixtures from Acorn®, Bradley®, Metcraft® and other manufacturers
- PERMEX® Synthetic Rubber Diaphragm with Dual Filtered Fixed Bypass
- Adjustable tailpiece accommodates various installation heights
- High chloramine resistant PERMEX synthetic rubber diaphragm with Linear Filtered Bypass and Vortex Cleansing Action
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037
- Battery powered
- Programmed to 2 activations in 5 minutes; 60 minutes lockout, custom programs available

DOWNLOADS

- [8603-ESM Installation Instructions](#)
- [8603-ESM Maintenance Guide](#)
- [Additional Downloads](#)