



Sloan® XLERATOR® Hand Dryer

EHD-501-ECO-MW-HEPA

Product description

EHD-501-ECO, HEPA, 110/120V, Sloan® XLERATOR® Sensor-Operated Wall-Mounted Hand Dryer.

Compliances & Certifications



(BAA Compliant, cUL Certified, EPD, Proposition 65, UL Certified, WELL Building Standard)

Code 3366100

Finish

 Matte White (MW)

Downloads

- [Sloan XLERATOR and Sloan XLERATOR Eco Hand Dryer Instructions .pdf](#)
- [Hand Dryer Brochure.pdf](#)
- [Additional Downloads](#)

Videos

- [Sloan – Company Overview](#)

Details

- Finish: Matte White (MW)
- Voltage: 110/120V
- Wattage: 50/60Hz
- Amperage: 4.3A-4.5A
- Mounting: Wall-Mounted
- Power Type: Hardwired
- Depth: 12.688" (170mm)
- Height: 12.688" (322mm)
- Width: 11.75" (298mm)

Features

- 35-second lockout feature if hands are not removed, 10 second dry time
- 95% cost savings vs. paper towels, Adjustable speed and sound (High-Low)
- Electric Specifications: 110-120V – 4.3-4.5 Amps, 460-530 Watts, 50/60 Hz, Can install multiple units on one circuit
- Externally visible Red LED light that flashes error codes to assist in troubleshooting and identify if filter has been clogged
- Hygienic hand drying solution, No Heat option
- Quantity Recommendations: 1 dryer for every 2 sink stations is sufficient for most applications. For high traffic applications we suggest 1 dryer per sink station.
- Suggested Mounting Heights for Ideal Performance (from floor to bottom of dryer): Men: 45" (114 cm), Women: 43" (109 cm), Teenagers: 41" (104 cm), Children: 35" (89 cm), ADA: 37" (94 cm).
Note: When mounting for any user ensure that it is mounted below the 48" ADA Maximum
- Vandal resistant cover design, Virtually maintenance free
- Weight: 15-17 lbs.
- Available with HEPA Filtration System proven to remove 99.97% of potentially present bacteria at 0.3 microns from the air

Recommended specifications

Sloan Xlerator Eco Sensor Operated Hand Dryer. 120V/110V Matte White Finish.

Warranty

[View Warranty Information](#)

Notes

All information contained within this document subject to change without notice.

